

**INDUSTRIAL COMPONENT DATA**

# 5SE2306 SIEMENS [NEOZED-Sicherungseinsatz], D01, 6 A, [gG], Un AC: 400 V, Un DC: 250 V, [mit verzinnten Kont..

Brand: SIEMENS | Manufacturer Part Number: 5SE2306



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 5SE2306             |
| Catalog number  | 10000               |
| Category        | D0-system fuse link |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-49A4FB62DA       |
| Generated       | 2026-08-05          |

## Product Overview

NEOZED fuse-link, D01, 6 A, gG, Un AC: 400 V, Un DC: 250 V, with tin-coated contact-caps  
NEOZED fuse cartridge, 400V, service class gL/gG, size D01, 6A, 10pcs box. easy individual extraction ( \*\* ATTENTION :  
Price per 1 Unit and Minimum Quantity / Multiplo order 10 Units \*\* )

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Fuses Neozed, Diazed, Silized, Minized**

## Additional Product Information

**Technical data**

NEOZED fuse-link, D01, 6 A, gG, Un AC: 400 V, Un DC: 250 V, with tin-coated contact-caps

**Model**

product brand name SENTRON

product designation NEOZED fuse link

design of the product With tin-coated contact caps

product variations Pack of 10

design of the fuse link NEOZED fuse link

**General technical data**

size of fuse system / according to EN 60269-1 D01

operating class of the fuse link gG

Supply voltage

supply voltage

? at AC / rated value 400 V

? at DC 250 V

operating voltage / rated value 400 V

protection class IP IP20, with connected conductors

switching capacity current / according to IEC 60947-2 / rated value 50 kA

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 1.4 W

operational current

? at 30 °C / rated value 5.88 A

? at 40 °C / rated value 5.7 A

? at 45 °C / rated value 5.52 A

? at 50 °C / rated value 5.4 A

? at 55 °C / rated value 5.28 A

? at 60 °C / rated value 5.16 A

? at AC / rated value 6 A

Main circuit

operational current / rated value 6 A

Appearance

color coding of the fuse link Green

breaking capacity maximum short-circuit current (Icu) / at AC / rated value 50 kA

Mechanical Design

mounting position Any, preferably vertical

net weight 6 g

ambient temperature / during operation

? minimum 40 °C

? maximum 40 °C

environmental category Up to 45°C at 95 % rel. humidity

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmation

UK Declaration of Conformity

Test Certifica...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SE2306 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.