

INDUSTRIAL COMPONENT DATA

5SE2350 SIEMENS [NEOZED-Sicherungseinsatz], D02, 50 A, [gG], Un AC: 400 V, Un DC: 250 V, [mit versilberten K..

Brand: SIEMENS | Manufacturer Part Number: 5SE2350



Manufacturer	SIEMENS
MPN / Reference	5SE2350
Catalog number	10000
Category	D0-system fuse link
Minimum order	10 Pcs
Document ID	EO-3CBC34D886
Generated	2026-08-02

Product Overview

NEOZED fuse-link, D02, 50 A, gG, Un AC: 400 V, Un DC: 250 V, with silver-coated contact-caps

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Fuses Neozed, Diazed, Silized, Minized**

Additional Product Information

Technical data

NEOZED fuse-link, D02, 50 A, gG, Un AC: 400 V, Un DC: 250 V, with silver-coated contact-caps

Model

product brand name SENTRON

product designation NEOZED fuse link

design of the product With silver-plated contact caps

product variations Pack of 10

design of the fuse link NEOZED fuse link

General technical data

size of fuse system / according to EN 60269-1 D02

operating class of the fuse link gG

Supply voltage

supply voltage

? at AC / rated value 400 V

? at DC 250 V

operating voltage / rated value 400 V

protection class IP IP20, with connected conductors

switching capacity current / according to IEC 60947-2 / rated value 50 kA

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 3.1 W

operational current

? at 30 °C / rated value 49 A

? at 40 °C / rated value 47.5 A

? at 45 °C / rated value 46 A

? at 50 °C / rated value 45 A

? at 55 °C / rated value 44 A

? at 60 °C / rated value 43 A

? at AC / rated value 50 A

Main circuit

operational current / rated value 50 A

Appearance

color coding of the fuse link White

breaking capacity maximum short-circuit current (Icu) / at AC / rated value 50 kA

Mechanical Design

mounting position Any, preferably vertical

net weight 14 g

ambient temperature / during operation

? minimum 40 °C

? maximum 40 °C

environmental category Up to 45°C at 95 % rel. humidity

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmation

UK Declaration of Conformity

Test Certifi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SE2350 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.