

## INDUSTRIAL COMPONENT DATA

# 5SG1302 SIEMENS NEOZED, fuse base, D01, 1-pole, 16 A, Un AC: 400 V, Un DC: 250 V without LED signal detector..

Brand: SIEMENS | Manufacturer Part Number: 5SG1302



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 5SG1302             |
| Catalog number  | 10000               |
| Category        | D0-system fuse base |
| Minimum order   | 15 Pcs              |
| Document ID     | EO-64517C7EBF       |
| Generated       | 2026-08-03          |

## Product Overview

NEOZED, fuse base, D01, 1-pole, 16 A, Un AC: 400 V, Un DC: 250 V without LED signal detector with frame terminal  
NEOZED, Fuse Holder, D01, à1pôles , 16 A, One AC: 400 V, One DC: 250 V ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 15 Units \*\* ). Manufactured to order. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Fuses Neozed, Diazed, Silized, Minized

## Additional Product Information

## Technical data

NEOZED, fuse base, D01, 1-pole, 16 A, Un AC: 400 V, Un DC: 250 V without LED signal detector with frame terminal  
Model

product brand name NEOZED

product designation Fuse base

design of the product NEOZED fuse base installation

## General technical data

number of poles 1

size of fuse system / according to EN 60269-1 D01

Supply voltage

operating voltage / rated value 400 V

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.2 W

**operational current**

? at 35 °C / rated value 15.36 A

? at 40 °C / rated value 15.04 A

? at 45 °C / rated value 14.72 A

? at 50 °C / rated value 14.4 A

? at 55 °C / rated value 14.08 A

? at 60 °C / rated value 13.76 A

? at 65 °C / rated value 13.28 A

? at 70 °C / rated value 12.96 A

**Main circuit**

operational current / rated value 16 A

**Product details**

product component / cover Yes

**Mechanical Design**

height 67 mm

width 27 mm

depth 55 mm

fastening method DIN rail

net weight 64 g

material / of D fuse base plastic

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation**

UK Declaration of Conformity

**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG1302>

Service&amp;Support (Manuals, Certificates, Characteristics,

FAQs,...)<https://support.industry.siemens.com/cs/ww/en/ps/5SG1302>

Ima...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 5SG1302 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.