

INDUSTRIAL COMPONENT DATA

5SG5302-1 SIEMENS NEOZED, fuse base, D01, 3-pole, 16 A, Un AC: 400 V, Un DC: 250 V with LED signal detector ..

Brand: SIEMENS | Manufacturer Part Number: 5SG5302-1



Manufacturer	SIEMENS
MPN / Reference	5SG5302-1
Catalog number	10000
Category	D0-system fuse base
Minimum order	5 Pcs
Document ID	EO-9C808A0868
Generated	2026-08-05

Product Overview

NEOZED, fuse base, D01, 3-pole, 16 A, Un AC: 400 V, Un DC: 250 V with LED signal detector with frame terminal
NEOZED, Fuse Base, D01, à3pôles, 16 A, One AC: 400 V, One DC: 250 V (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 5 Units **). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Fuses Neozed, Diazed, Silized, Minized

Additional Product Information

Technical data

NEOZED, fuse base, D01, 3-pole, 16 A, Un AC: 400 V, Un DC: 250 V with LED signal detector with frame terminal

Model

product brand name NEOZED

product designation Fuse base

design of the product NEOZED fuse base installation

General technical data

number of poles 3

size of fuse system / according to EN 60269-1 D01

Supply voltage

operating voltage / rated value 400 V

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.6 W

operational current

? at 35 °C / rated value 15.36 A

? at 40 °C / rated value 15.04 A

? at 45 °C / rated value 14.72 A

? at 50 °C / rated value 14.4 A

? at 55 °C / rated value 14.08 A

? at 60 °C / rated value 13.76 A

? at 65 °C / rated value 13.28 A

? at 70 °C / rated value 12.96 A

Main circuit

operational current / rated value 16 A

Product details

product component / cover Yes

Mechanical Design

height 67 mm

width 81 mm

depth 55 mm

fastening method DIN rail

net weight 192 g

material / of D fuse base plastic

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

UK Declaration of Conformity

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG5302-1>

Service&Support (Manuals, Certificates, Characteristics,

FAQs,...)<https://support.industry.siemens.com/cs/ww/en/ps/5SG5302-1>

I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SG5302-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.