

INDUSTRIAL COMPONENT DATA

5SG5693 SIEMENS NEOZED, fuse base, D02, 3-pole, 63 A, Un AC: 400 V, Un DC: 250 V incoming terminal: screw he..

Brand: SIEMENS | Manufacturer Part Number: 5SG5693



Manufacturer	SIEMENS
MPN / Reference	5SG5693
Catalog number	10000
Category	D0-system fuse base
Minimum order	2 Pcs
Document ID	EO-2CC69DC89B
Generated	2026-08-05

Product Overview

NEOZED, fuse base, D02, 3-pole, 63 A, Un AC: 400 V, Un DC: 250 V incoming terminal: screw head contact outgoing terminal: saddle terminal

NEOZED fuse base, ceramic, tam. D02/63A, 3 poles, 4.5 mode, pressure fixing, with lid (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiplication 2 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Fuses Neozed, Diazed, Silized, Minized

Additional Product Information

Technical data

NEOZED, fuse base, D02, 3-pole, 63 A, Un AC: 400 V, Un DC: 250 V incoming terminal: screw head contact outgoing terminal: saddle terminal

Model

product brand name NEOZED

product designation Fuse base

design of the product NEOZED fuse base installation

General technical data

number of poles 3

size of fuse system / according to EN 60269-1 D02

Supply voltage

operating voltage / rated value 400 V

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 3 W

operational current

? at 35 °C / rated value 60.48 A

? at 40 °C / rated value 59.22 A

? at 45 °C / rated value 57.96 A

? at 50 °C / rated value 56.7 A

? at 55 °C / rated value 55.44 A

? at 60 °C / rated value 54.18 A

? at 65 °C / rated value 52.29 A

? at 70 °C / rated value 51.03 A

Main circuit

operational current / rated value 63 A

Product details

product component / cover Yes

Mechanical Design

height 60 mm

width 80.8 mm

depth 41 mm

fastening method DIN rail

net weight 271 g

material / of D fuse base porcelain

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

UK Declaration of Conformity

Miscellaneous**Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG5693>Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<https://support.industry.siemens...>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 5SG5693 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.