

## INDUSTRIAL COMPONENT DATA

# 5SG7153 SIEMENS MINIZED, Switch disconnecter with Fuse, D02, 1P+N, In: 63 A, Un AC: 230 V

Brand: SIEMENS | Manufacturer Part Number: 5SG7153



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 5SG7153                       |
| Catalog number  | 10000                         |
| Category        | D0-system switch disconnecter |
| Minimum order   | 2 Pcs                         |
| Document ID     | EO-8C56592CC9                 |
| Generated       | 2026-08-03                    |

## Product Overview

MINIZED, Switch disconnecter with Fuse, D02, 1P+N, In: 63 A, Un AC: 230 V

Switch-fuse MINIZED 70mm, p/cartridges NEOZED tam. D02/63A, 1 pole+N, 3 mode, insertable technique. Cancellations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Fuses Neozed, Diazed, Silized, Minized

## Additional Product Information

Technical data

MINIZED, Switch disconnecter with Fuse, D02, 1P+N, In: 63 A, Un AC: 230 V

Model

product brand name MINIZED

product designation Switch disconnectors with fuses

General technical data

number of poles 2

number of poles / note 1P+N

size of fuse system / according to EN 60269-1 D02

overvoltage category 4

Voltage

surge voltage resistance / rated value 6 kV

Supply voltage

operating voltage / at AC / rated value 230 V

Protection class

protection class IP IP20, with connected conductors

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 4 W

Current

operational current / at AC / rated value 63 A

Product details

product feature / sealable Yes

Connections

tightening torque / with screw-type terminals

? minimum 2.5 N·m

? maximum 3 N·m

Mechanical Design

height 70 mm

width 54 mm

depth 90 mm

mounting position any, preferably vertical

net weight 291 g

Downloads and manuals

General Product Approval Declaration of Conformity Test Certificates

Confirmation

UK Declaration of Conformity

Type Test Certificates/Test Report

Marine / Shipping other

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7153>

Service&Support (Manuals, Certificates, Characteristics,

FAQs,...)<https://support.industry.siemens.com/cs/ww/en/ps/5SG7153>

Image database (product i...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SG7153 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.