

**INDUSTRIAL COMPONENT DATA**

# 5SG7611-0KK06 SIEMENS MINIZED, fuse switch disconnecter, D01, 1-pole, In: 6 A, Un AC: 230 V

Brand: SIEMENS | Manufacturer Part Number: 5SG7611-0KK06



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 5SG7611-0KK06                 |
| Catalog number  | 76110                         |
| Category        | D0-system switch disconnecter |
| Minimum order   | 12 Pcs                        |
| Document ID     | EO-7000F72772                 |
| Generated       | 2026-08-05                    |

## Product Overview

MINIZED, fuse switch disconnecter, D01, 1-pole, In: 6 A, Un AC: 230 V

MINIZED SECTIONERS D01 6A 1P ( \*\* ATTENTION : Price per 1 Unit and Quantity Minimum/Multiplo Order 12 Units \*\* ).  
Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Fuses Neozed, Diazed, Silized, Minized

## Additional Product Information

Technical data

MINIZED, fuse switch disconnecter, D01, 1-pole, In: 6 A, Un AC: 230 V

Model

product brand name MINIZED

product designation Fuse switch disconnecter

General technical data

number of poles 1

size of fuse system / according to EN 60269-1 D01

overvoltage category 4

Voltage

surge voltage resistance / rated value 6 kV

Supply voltage

operating voltage / at AC / rated value 230 V

**Protection class**

protection class IP IP20, with connected conductors

**Dissipation**

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.1 W

**Current**

operational current / at AC / rated value 6 A

**Product details**

product feature / sealable Yes

**Connections**

tightening torque / with screw-type terminals

? minimum 2.5 N·m

? maximum 3 N·m

**Mechanical Design**

height 70 mm

width 18 mm

depth 88 mm

mounting position any, preferably vertical

net weight 67 g

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation**

UK Declaration of Conformity

**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...) <http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7611-0KK06>

Service&amp;Support (Manuals, Certificates, Characteristics,

FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/5SG7611-0KK06>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,  
...) <http://www.automation.siemens.com>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 5SG7611-0KK06 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](http://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.