

INDUSTRIAL COMPONENT DATA

5SM3318-6KK SIEMENS Residual current operated circuit breaker, 2-pole, type A, In: 100 A, 30 mA, Un AC: 230 V

Brand: SIEMENS | Manufacturer Part Number: 5SM3318-6KK



Manufacturer	SIEMENS
MPN / Reference	5SM3318-6KK
Catalog number	33186
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-FE3E4D5BBA
Generated	2026-08-04

Product Overview

Residual current operated circuit breaker, 2-pole, type A, In: 100 A, 30 mA, Un AC: 230 V

Differential switch class A, 2.5 mod., 2 poles, 100 A, 30 mA. Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Industrial differential switches from 8

Additional Product Information

Technical data

Residual current operated circuit breaker, 2-pole, type A, In: 100 A, 30 mA, Un AC: 230 V

Model

product brand name SENTRON

product designation RCCB

design of the product Instantaneous

General technical data

number of poles 2

size of installation devices / according to DIN 43880 1

mechanical service life (switching cycles) / typical 10 000

short-circuit current rating 10 kA

switching function / short-term delayed No

overvoltage category III

Supply voltage

supply voltage

? at AC / rated value 230 V

? for testing equipment / minimum 100 V

value range / of the supply voltage frequency 50 Hz

operating frequency 50 Hz

supply voltage frequency / rated value 50 Hz

value range / of the operating frequency 50 Hz

value range / of the supply voltage / at AC 230 V

Protection class

protection class IP IP20, if the distribution board is installed, with connected conductors

Switching capacity

switching capacity current

? according to EN 60898 / rated value 1 kA

? according to IEC 61008-1 / rated value 1 kA

Current

tripping fault current / rated value 30 mA

operational current

? at AC / rated value 100 A

residual current type A

surge current resistance / rated value 1 kA

Product details

product feature / silicon-free Yes

product extension / installable / supplementary devices Yes

Connections

connectable conductor cross-section / solid

? minimum 1.5 mm²

? maximum 50 mm²

connectable conductor cross-section / stranded

? minimum 1.5 mm²

? maximum 50 mm²

tightening torque / with sc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SM3318-6KK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.