

INDUSTRIAL COMPONENT DATA

5ST3014 SIEMENS Auxiliary current switch low power rating, 2 NO for miniature circuit breaker 5SL, 5SY, 5SP ..

Brand: SIEMENS | Manufacturer Part Number: 5ST3014



Manufacturer	SIEMENS
MPN / Reference	5ST3014
Catalog number	10000
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-13C1591BFD
Generated	2026-08-05

Product Overview

Auxiliary current switch low power rating, 2 NO for miniature circuit breaker 5SL, 5SY, 5SP Incorporated switch 5TL1, RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)

Auxiliary contacts (AS) p/automatic 5SY and 5SP4, 0.5 mód., 2NA, p/small powers. Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems
--------------	---

Additional Product Information

Technical data

Auxiliary current switch low power rating, 2 NO for miniature circuit breaker 5SL, 5SY, 5SP Incorporated switch 5TL1, RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)

Model

product brand name SENTRON

product designation Auxiliary current switch

design of the product Mountable

design of the product / factory mounted No

electrical endurance (switching cycles) / typical 10 000

Voltage

insulation voltage / rated value 50 V

surge voltage resistance / rated value 0.8 kV

Supply voltage

supply voltage / at DC / rated value

? minimum 5 V

operating voltage

? rated value 30 V

? at DC / rated value / minimum 5 V

protection class IP IP20

Switching capacity

switching capacity current / rated value 0 A

Control current

type of voltage / of control voltage DC

Product details

product component

? auxiliary switch Yes

number of fault signal contacts 0

number of NC contacts 0

number of NO contacts 2

number of CO contacts 0

product extension / can be mounted Universal

product extension auxiliary switch

Connections

connectable conductor cross-section

? minimum 0.5 mm²

? maximum 2.5 mm²

tightening torque / with screw-type terminals

? maximum 1 N·m

type of connectable conductor cross-sections / at AWG cables 24 ... 12

Mechanical Design

height 90 mm

width 9 mm

depth 70 mm

number of modular width units 0.5

net weight 67 g

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

ambient temperature / during storage

? minimum permis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5ST3014 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.