

INDUSTRIAL COMPONENT DATA

5SU1354-7VK32 SIEMENS RCBO, 10 kA, 1P+N, type A, short-time-delayed K, 30 mA, C-Char, In: 32 A, Un AC: 230 V

Brand: SIEMENS | Manufacturer Part Number: 5SU1354-7VK32



Manufacturer	SIEMENS
MPN / Reference	5SU1354-7VK32
Catalog number	13547
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-C9DFE98663
Generated	2026-08-05

Product Overview

RCBO, 10 kA, 1P+N, type A, short-time-delayed K, 30 mA, C-Char, In: 32 A, Un AC: 230 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Tertiary differential switches up to 80

Additional Product Information

ETIM: EC000905 - Earth leakage circuit breaker

Value Unit

Disconnection characteristic (EF012587) -

Number of poles (total) (EF008618) 2

Number of protected poles (EF005548) 1

Rated voltage (EF000228) 230 V

Rated insulation voltage U_i (EF001366) 264 VRated impulse withstand voltage U_{imp} (EF011980) 4.0 kV

Rated current (EF000227) 32 A

Rated fault current (EF002358) 0.03 A

Leakage current type (EF002560) A

Current limiting class (EF002568) 3

Rated short-circuit breaking capacity according to EN 61009 (EF012628) 10.0 kA

Rated short-circuit breaking capacity IEC 60947-2 (EF006065) 15.0 kA

Rated short-circuit breaking capacity I_{cn} according to EN 61009-1 (EF011981) 10.0 kA

Surge current capacity (EF002564) 3.0 kA
Voltage type (EF000187) AC
Frequency (EF005455) 50 Hz
Release characteristic (EF000889) C
Concurrently switching N-neutral (EF005997) true
With interlocking device (EF007385) true
Over voltage category (EF002569) 3
Pollution degree (EF002570) 2
Ambient temperature during operating (EF007515) [-25', '55'] °C
Width in number of modular spacings (EF002950) 2
Built-in depth (EF000218) 70.0 mm
Suitable for flush-mounted installation (EF006573) true
Anti-nuisance tripping version (EF009497) true
Degree of protection (IP) (EF005474) IP20
Connectable conductor cross section solid-core (EF007337) [0.75', '35.0'] mm²
Connectable conductor cross section multi-wired (EF007343) [0.75', '35.0'] mm²
RCBO, 10 kA, 1P+N, type A, short-time-delayed K, 30 mA, C-Char, In: 32 A, Un AC: 23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SU1354-7VK32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.