

## INDUSTRIAL COMPONENT DATA

# 5SV3614-8 SIEMENS Residual current operated circuit breaker, 2-pole, type A, selective, In: 40 A, 300 mA, Un..

Brand: SIEMENS | Manufacturer Part Number: 5SV3614-8



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 5SV3614-8                               |
| Catalog number  | 36148                                   |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-CB97522691                           |
| Generated       | 2026-08-03                              |

## Product Overview

Residual current operated circuit breaker, 2-pole, type A, selective, In: 40 A, 300 mA, Un AC: 230 V  
DIFFERENTIAL SWITCH TYPE A 40A 1+N POL. 300MA 230V 2MOD. SELECTIVE. Cancellations and returns limited.  
Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                                   |
|--------------|---------------------------------------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Tertiary differential switches up to 80 |
|--------------|---------------------------------------------------------------------------------------------------|

## Additional Product Information

## Technical data

Residual current operated circuit breaker, 2-pole, type A, selective, In: 40 A, 300 mA, Un AC: 230 V

## Model

product brand name SENTRON

product designation RCCB

design of the product Selective

## General technical data

number of poles 2

size of installation devices / according to DIN 43880 1

mechanical service life (switching cycles) / typical 10 000

short-circuit current / of series fuse / maximum permissible 80 A

short-circuit current rating 10 kA

switching function / short-term delayed No

overvoltage category III

Supply voltage

supply voltage / for testing equipment / minimum 100 V

value range / of the supply voltage frequency 50 Hz

value range / of the operating frequency 50/60 Hz

value range / of the supply voltage / at AC 230/400 V

Protection class

protection class IP IP20, if the distribution board is installed, with connected conductors

Switching capacity

switching capacity current

? according to IEC 61008-1 / rated value 0.5 kA

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 1 W

? maximum 2 W

Current

tripping fault current / rated value 300 mA

operational current

? at 40 °C / rated value 40 A

? at 45 °C / rated value 38.1 A

? at 50 °C / rated value 35.59 A

? at 55 °C / rated value 32.29 A

? at 60 °C / rated value 28.19 A

? at 65 °C / rated value 23.3 A

? at 70 °C / rated value 17.6 A

? at AC / rated value 40 A

residual current type A

let-through current / permissible 5 200 A

I<sub>2t</sub> value / permissible 58...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SV3614-8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.