

INDUSTRIAL COMPONENT DATA

5SV3616-3 SIEMENS Residual current operated circuit breaker, 2-pole, type F, short-time delayed, In: 63 A, 3..

Brand: SIEMENS | Manufacturer Part Number: 5SV3616-3



Manufacturer	SIEMENS
MPN / Reference	5SV3616-3
Catalog number	36163
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-73AF8476E0
Generated	2026-08-06

Product Overview

Residual current operated circuit breaker, 2-pole, type F, short-time delayed, In: 63 A, 300 mA, Un AC: 230 V
DIFFERENTIAL SWITCH TYPE F 63A 1+N POL. 300MA 230V 2MOD.. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Tertiary differential switches up to 80

Additional Product Information

Technical data

Residual current operated circuit breaker, 2-pole, type F, short-time delayed, In: 63 A, 300 mA, Un AC: 230 V

Model

product brand name SENTRON

product designation RCCB

design of the product Short-time delayed

General technical data

number of poles 2

size of installation devices / according to DIN 43880 1

mechanical service life (switching cycles) / typical 10 000

short-circuit current / of series fuse / maximum permissible 80 A

short-circuit current rating 10 kA

switching function / short-term delayed Yes

overvoltage category III

Supply voltage

supply voltage / for testing equipment / minimum 100 V

value range / of the supply voltage frequency 50 Hz

value range / of the operating frequency 50/60 Hz

value range / of the supply voltage / at AC 230/400 V

Protection class

protection class IP IP20, if the distribution board is installed, with connected conductors

Switching capacity

switching capacity current

? according to IEC 61008-1 / rated value 0.8 kA

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 2.7 W

? maximum 5.4 W

Current

tripping fault current / rated value 300 mA

operational current

? at 40 °C / rated value 63 A

? at 45 °C / rated value 63 A

? at 50 °C / rated value 63 A

? at 55 °C / rated value 63 A

? at 60 °C / rated value 63 A

? at 65 °C / rated value 56.96 A

? at 70 °C / rated value 48.2 A

? at AC / rated value 63 A

residual current type F

let-through current / permissible 7 100 A

I2t value / p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SV3616-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.