

## INDUSTRIAL COMPONENT DATA

# 5SY5232-6 SIEMENS Circuit breaker Universal current 440 V DC 400 V AC 10kA, 2-pole, B, 32A

Brand: SIEMENS | Manufacturer Part Number: 5SY5232-6



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | SIEMENS                         |
| MPN / Reference | 5SY5232-6                       |
| Catalog number  | 52326                           |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-BC3BE752C8                   |
| Generated       | 2026-08-06                      |

## Product Overview

Circuit breaker Universal current 440 V DC 400 V AC 10kA, 2-pole, B, 32A

Int aut univ acces 70mm 10kA 2poles B-32A. Manufactured to order. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Industrial circuit breakers from 6 kA

## Additional Product Information

## Technical data

Circuit breaker Universal current 440 V DC 400 V AC 10kA, 2-pole, B, 32A

## Model

product brand name SENTRON

product designation Miniature circuit breaker

## General technical data

number of poles 2

design of pole 2P

tripping characteristic class B

mechanical service life (switching cycles) / typical 10 000

overvoltage category III

degree of pollution 3

## Voltage

type of voltage / of the operating voltage AC/DC

insulation voltage (Ui)

? at DC / rated value 250 V

? with single-phase operation / at AC / rated value 440 V

? with multi-phase operation / at AC / rated value 440 V

Supply voltage

supply voltage

? at AC / rated value 400 V

? at DC / rated value 440 V

value range / of the supply voltage frequency 50/60 Hz

operating voltage / at DC / rated value / maximum 500 V

Protection class

protection class IP IP20, with connected conductors

Switching capacity

switching capacity current

? at DC / according to IEC 60947-2 / rated value 15 kA

? according to EN 60898 / rated value 10 kA

energy limitation class 3

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 2.6 W

Current

operational current

? at 35 °C / rated value 32 A

? at 40 °C / rated value 30.46 A

? at 45 °C / rated value 29.66 A

? at 50 °C / rated value 28.86 A

? at 55 °C / rated value 28 A

? at 60 °C / rated value 27.14 A

? at AC / rated value 32 A

suitability for operation universal current

Product details

product component / neutral conductor switching No

produ...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SY5232-6 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.