

INDUSTRIAL COMPONENT DATA

5SY6305-7 SIEMENS Miniature circuit breaker 400 V 6kA, 3-pole, C, 0.5A, D 70 mm

Brand: SIEMENS | Manufacturer Part Number: 5SY6305-7



Manufacturer	SIEMENS
MPN / Reference	5SY6305-7
Catalog number	63057
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A80B23EFEC
Generated	2026-08-06

Product Overview

Miniature circuit breaker 400 V 6kA, 3-pole, C, 0.5A, D=70 mm

Circuit breaker, 70mm, accessory, 6kA, curve C, 3 poles, 0.5A. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Tertiary circuit breakers from 6 kA
--------------	---

Additional Product Information

Technical data

Miniature circuit breaker 400 V 6kA, 3-pole, C, 0.5A, D=70 mm

Model

product brand name SENTRON

product designation Miniature circuit breaker

General technical data

number of poles 3

design of pole 3P

tripping characteristic class C

mechanical service life (switching cycles) / typical 10 000

overvoltage category III

degree of pollution 3

Voltage

type of voltage / of the operating voltage AC

insulation voltage (Ui)

? with single-phase operation / at AC / rated value 440 V

? with multi-phase operation / at AC / rated value 440 V

supply voltage / with single-phase operation / at AC / rated value 230 V

Supply voltage

supply voltage

? at AC / rated value 400 V

value range / of the supply voltage frequency 50/60 Hz

operating voltage / at DC / rated value / maximum 72 V

Protection class

protection class IP IP20, with connected conductors

Switching capacity

switching capacity current

? at DC / according to IEC 60947-2 / rated value 15 kA

? according to EN 60898 / rated value 6 kA

? according to IEC 60947-2 / rated value 30 kA

energy limitation class 3

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.8 W

Current

operational current

? at 35 °C / rated value 0.5 A

? at 40 °C / rated value 0.48 A

? at 45 °C / rated value 0.46 A

? at 50 °C / rated value 0.45 A

? at 55 °C / rated value 0.44 A

? at AC / rated value 0.5 A

suitability for operation Mechanical engineering / industry

Product details

product component / neut...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5SY6305-7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.