

**INDUSTRIAL COMPONENT DATA**

# 5TE1640 SIEMENS Disconnecter, T92 690 V 200 A 3-pole+NF transparent

Brand: SIEMENS | Manufacturer Part Number: 5TE1640



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 5TE1640             |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-507264E7E5       |
| Generated       | 2026-08-02          |

## Product Overview

Disconnecter, T92 690 V 200 A 3-pole+NF transparent

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems**

## Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated operating voltage (EF001435) - V

Suitable for front mounting 4-hole (EF007247) -

Degree of protection (NEMA) (EF011959) -

Rated short-time withstand current I<sub>cw</sub> (EF007050) - kA

Rated operation power at AC-3, 400 V (EF001364) - kW

Rated permanent current at AC-21, 400 V (EF009165) - A

Suitable for intermediate mounting (EF007264) -

Number of switches (EF005586) -

Switching power at 400 V (EF009166) - kW

Suitable for front mounting centre (EF007248) -

Conditioned rated short-circuit current I<sub>q</sub> (EF001444) - kA

Colour control element (EF007167) -

Suitable for floor mounting (EF007243) -

Version as reversing switch (EF009408) -  
Rated permanent current at AC-23, 400 V (EF011777) - A  
Suitable for distribution board installation (EF007262) -  
Version as main switch (EF006981) false  
Version as maintenance-/service switch (EF006986) true  
Version as safety switch (EF006985) false  
Version as emergency stop installation (EF006959) false  
Max. rated operation voltage Ue AC (EF007355) 690 V  
Rated permanent current Iu (EF001389) 200.0 A  
Rated operation power at AC-23, 400 V (EF007027) 88.0 kW  
Number of poles (EF001391) 3  
Number of auxiliary contacts as normally closed contact (EF001377) 0  
Number of auxiliary contacts as normally open contact (EF001376) 3  
Number of auxiliary contacts as change-over contact (EF003531) 0  
Motor drive optional (EF007386) false  
Motor drive integrated (EF006697) false  
Voltage release optional (EF007491) false  
Dev...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TE1640 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.