

INDUSTRIAL COMPONENT DATA

5TE4841 SIEMENS button, 1 NO+1 NC 20 A 2 keys red green, lamps 230 V

Brand: SIEMENS | Manufacturer Part Number: 5TE4841



Manufacturer	SIEMENS
MPN / Reference	5TE4841
Catalog number	10000
Category	Push button for distribution board
Minimum order	1 Pcs
Document ID	EO-F84823EEEE
Generated	2026-08-03

Product Overview

button, 1 NO+1 NC 20 A 2 keys red green, lamps 230 V

Double lum pushbutton 70mm, red + gray buttons, 400V, 1 mode, cont mant, p / max 5m count, 2X (1NA), 20A.

Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems

Additional Product Information

Technical data

button, 1 NO+1 NC 20 A 2 keys red green, lamps 230 V

Model

product brand name SENTRON

product designation Pushbutton

design of the product 1 NO contact and 1 NC contact

type of light source LED

socket design / for light source others

mechanical service life (switching cycles) / typical 25 000

type of voltage / of the operating voltage AC

surge voltage resistance / rated value 4 kV

Supply voltage

operating voltage / rated value 400 V

Protection class

protection class IP IP20

making capacity current 60 A

breaking capacity current 60 A

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 0.6 W

? maximum 0.6 W

Current

operational current / at AC / rated value 20 A

Appearance

color

? of the button others

Product details

product component / signal lamp Yes

number of NC contacts 1

number of NO contacts 1

number of CO contacts 0

Display and operation

number of keys 1

connectable conductor cross-section / for flexible conductor / with core end processing

? minimum 1 mm²? maximum 6 mm²

connectable conductor cross-section / for rigid conductor

? minimum 1 mm²? maximum 6 mm²

tightening torque / with screw-type terminals

? minimum 0.8 N·m

? maximum 1 N·m

Mechanical Design

height 90 mm

depth 70 mm

installation depth 70 mm

number of modular width units 1

net weight 94 g

ambient temperature / during operation

? minimum -5 °C

? maximum 40 °C

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TE4841 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.