

INDUSTRIAL COMPONENT DATA

5TE8118 SIEMENS OFF switch 20 A 3 NO+N with auxiliary current switch 1 NO + 1 NC

Brand: SIEMENS | Manufacturer Part Number: 5TE8118



Manufacturer	SIEMENS
MPN / Reference	5TE8118
Catalog number	10000
Category	Main switch for distribution board
Minimum order	1 Pcs
Document ID	EO-470D1793EB
Generated	2026-08-02

Product Overview

OFF switch 20 A 3 NO+N with auxiliary current switch 1 NO + 1 NC

Switch 70mm, 230V, 1.5 mód., 6mm², 3 poles+N c/cont aux 1NA+1NC, 20A. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems

Additional Product Information

Technical data

OFF switch 20 A 3 NO+N with auxiliary current switch 1 NO + 1 NC

Model

product brand name SENTRON

product designation On/Off switches

design of the product 3 NO + N

design of the switching function Off switches

General technical data

number of poles 1

short-circuit current rating 10 kA

type of voltage / of the operating voltage AC

Supply voltage

operating voltage / rated value 400 V

Protection class

protection class IP Other

Switching capacity

switching capacity current / rated value 0.06 kA

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.7 W

Main circuit

operational current / rated value 20 A

Product details

product component / signal lamp No

number of NO contacts 3

Product function

product function / positive opening (acc. to DIN VDE 0113) No

connectable conductor cross-section / for flexible conductor / with core end processing

? minimum 1 mm²? maximum 6 mm²

connectable conductor cross-section / for rigid conductor

? minimum 1 mm²? maximum 6 mm²

tightening torque / with screw-type terminals

? minimum 0.8 N·m

? maximum 1 N·m

Mechanical Design

height 90 mm

depth 27 mm

installation depth 70 mm

number of modular width units 1.5

net weight 150 g

ambient temperature / during operation

? minimum -5 °C

? maximum 40 °C

ambient temperature / during storage / minimum -25 °C

Downloads and manuals

General Product Approval Declaration of Conformity Test Certificates

Confirmation

UK Declaration of Conformity

Misc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TE8118 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.