

## INDUSTRIAL COMPONENT DATA

## 5TE8151 SIEMENS Two-way switch 20 A 1 NO 1 NC

Brand: SIEMENS | Manufacturer Part Number: 5TE8151



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | SIEMENS                            |
| MPN / Reference | 5TE8151                            |
| Catalog number  | 10000                              |
| Category        | Main switch for distribution board |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-72DF2CA222                      |
| Generated       | 2026-08-01                         |

## Product Overview

Two-way switch 20 A 1 NO 1 NC

Switch 70mm, 230V/400V, 1 mode, 1NA+1NC, 20A. Cancellations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Other Modular Systems

## Additional Product Information

Technical data

Two-way switch 20 A 1 NO 1 NC

Model

product brand name SENTRON

product designation Two-way switches

design of the product 1 NO 1NC

design of the switching function Two-way switches

General technical data

number of poles 1

short-circuit current rating 10 kA

type of voltage / of the operating voltage AC

Supply voltage

operating voltage / rated value 400 V

Protection class

protection class IP Other

**Switching capacity**

switching capacity current / rated value 0.06 kA

**Dissipation**

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.7 W

**Main circuit**

operational current / rated value 20 A

**Product details**

product component / signal lamp No

number of NC contacts 1

number of NO contacts 1

**Product function**

product function / positive opening (acc. to DIN VDE 0113) No

connectable conductor cross-section / for flexible conductor / with core end processing

? minimum 1 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / for rigid conductor

? minimum 1 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

tightening torque / with screw-type terminals

? minimum 0.8 N·m

? maximum 1 N·m

**Mechanical Design**

height 90 mm

depth 17.6 mm

installation depth 70 mm

number of modular width units 1

net weight 75 g

ambient temperature / during operation

? minimum -5 °C

? maximum 40 °C

ambient temperature / during storage / minimum -25 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity

**Confirmation**

UK Declaration of Conformity

Test Certificates other

Type....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TE8151 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.