

**INDUSTRIAL COMPONENT DATA**

# 5TE8218 SIEMENS OFF switch 32 A 3 NO+N Terminal 6 mm2 with auxiliary current switch 1 NO + 1 NC

Brand: SIEMENS | Manufacturer Part Number: 5TE8218



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | SIEMENS                            |
| MPN / Reference | 5TE8218                            |
| Catalog number  | 10000                              |
| Category        | Main switch for distribution board |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-21F177F63D                      |
| Generated       | 2026-08-01                         |

## Product Overview

OFF switch 32 A 3 NO+N Terminal 6 mm2 with auxiliary current switch 1 NO + 1 NC

Switch 70mm, 230V, 1.5 mode, 6mm2, 3 poles+N w/cont aux 1NA+1NC, 32A. Cancellations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems**

## Additional Product Information

**Technical data**

OFF switch 32 A 3 NO+N Terminal 6 mm2 with auxiliary current switch 1 NO + 1 NC

**Model**

product brand name SENTRON

product designation On/Off switches

design of the product 3 NO + N

design of the switching function Off switches

**General technical data**

number of poles 1

short-circuit current rating 10 kA

type of voltage / of the operating voltage AC

Supply voltage

operating voltage / rated value 400 V

**Protection class**

protection class IP Other

**Switching capacity**

switching capacity current / rated value 0.096 kA

**Dissipation**

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 0.7 W

**Main circuit**

operational current / rated value 32 A

**Product details**

product component / signal lamp No

number of NO contacts 3

**Product function**

product function / positive opening (acc. to DIN VDE 0113) No

connectable conductor cross-section / for flexible conductor / with core end processing

? minimum 1 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / for rigid conductor

? minimum 1 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

tightening torque / with screw-type terminals

? minimum 0.8 N·m

? maximum 1 N·m

**Mechanical Design**

height 90 mm

depth 27 mm

installation depth 70 mm

number of modular width units 1.5

net weight 148 g

ambient temperature / during operation

? minimum -5 °C

? maximum 40 °C

ambient temperature / during storage / minimum -25 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity Test Certificates

Confirmation

UK Declaration of...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 5TE8218 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.