

**INDUSTRIAL COMPONENT DATA**

# 5TT3415 SIEMENS Voltage relays AC 230/400V 0.85 2 CO contacts Response delay 0.5 s Return transfer delay 60 ..

Brand: SIEMENS | Manufacturer Part Number: 5TT3415



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | SIEMENS                  |
| MPN / Reference | 5TT3415                  |
| Catalog number  | 10000                    |
| Category        | Voltage monitoring relay |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-A834B3A328            |
| Generated       | 2026-08-03               |

## Product Overview

Voltage relays AC 230/400V 0.85 2 CO contacts Response delay 0.5 s Return transfer delay 60 s Test key 1, 2 OR 3-PHASE MONITORING RELAY WITH RESPECT TO N. THRESHOLD 0.85 NOT ADJUSTABLE, FIXED RESPONSE TIME 0.5S, FIXED RESET TIME AT 60S 2 SWITCHED. Cancellations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems**

## Additional Product Information

**Technical data**

Voltage relays AC 230/400V 0.85 2 CO contacts Response delay 0.5 s Return transfer delay 60 s Test key

Model

product brand name SENTRON

product designation Voltage relay

**General technical data**

adjustable pickup delay time / initial value 0.5 s

measurable voltage / at AC / initial value 195.5 V

**Voltage**

type of voltage / of the operating voltage / for actuation AC

type of voltage / for monitoring AC

adjustable voltage range / full-scale value 195.5 V

measurable voltage / at AC / full-scale value 264.5 V

**Current**

adjustable voltage range / initial value 195.5 V

**Control current**

control supply voltage

? at AC / at 50 Hz / rated value / minimum 195.5 V

? at AC / at 50 Hz / rated value / maximum 264.5 V

? at AC / at 60 Hz / rated value / minimum 195.5 V

? at AC / at 60 Hz / rated value / maximum 264.5 V

**Auxiliary circuit**

number of CO contacts / for auxiliary contacts 2

number of NC contacts / for auxiliary contacts 0

number of NO contacts / for auxiliary contacts 0

**Adjustable parameters**

adjustable pickup delay time / full-scale value 0.5 s

adjustable OFF-delay time

? initial value 60 s

? full-scale value 60 s

**Product function**

product function

? voltage window recognition 1 phase No

? voltage window recognition 3 phase No

? voltage window recognition DC No

? overvoltage detection 1 phase No

? overvoltage detection 3 phase No

? overvoltage detection DC No

? undervoltage detection 1 phase Yes

? undervoltage detection 3 phases Yes

? undervoltage detection DC No

**Connection...****REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 5TT3415 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.