

INDUSTRIAL COMPONENT DATA

5TT4122-0 SIEMENS Remote control switch with 2 NO contacts, with central ON/OFF function Contact for 230 V A..

Brand: SIEMENS | Manufacturer Part Number: 5TT4122-0



Manufacturer	SIEMENS
MPN / Reference	5TT4122-0
Catalog number	41220
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-819406A733
Generated	2026-08-02

Product Overview

Remote control switch with 2 NO contacts, with central ON/OFF function Contact for 230 V AC, 400V 16A Control 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems

Additional Product Information

Technical data

Remote control switch with 2 NO contacts, with central ON/OFF function Contact for 230 V AC, 400V 16A Control 230 V AC

Model

product brand name SENTRON

product designation Remote control switch

latching relay design mechanical for central control

General technical data

electrical endurance (switching cycles) 50 000

galvanic isolation / between magnet coil and contact Yes

switching voltage / of the contacts / at AC / minimum 10 V

switching current / at AC / per contact / minimum 100 mA

power loss [V•A] / of magnet coil / with pulse / rated value 7 VA

Voltage

type of voltage / of the operating voltage AC

continuous voltage fuse version Yes

operating range factor control supply voltage rated value / at AC / at 50 Hz

? initial value 0.8

? full-scale value 1.1

surge voltage resistance / rated value 4 kV

supply voltage 250 V

Supply voltage

supply voltage / minimum 250 V

Protection class

protection class IP IP20, with connected conductors

Switching capacity

switching capacity apparent power

? for fluorescent lamp load with DUO circuit 700 VA

? for fluorescent lamp load with parallel compensation 300 VA

? for uncompensated fluorescent lamp load 400 VA

switching capacity current

? at cos phi 0.6 16 A

? rated value 16 A

switching capacity active power / with incandescent lamp load 2 000 W

Dissipation

power loss [W]

? at 16 A / per contact / rated value 1.2 W

? of magnet coil / with pulse / rated value 4.5 W

switching current

? with glow lamp load / with 5TT4 920 compens...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT4122-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.