

INDUSTRIAL COMPONENT DATA

5TT4123-0 SIEMENS Remote control switch with 3 NO contacts with central ON/OFF function Contact for 230 V AC..

Brand: SIEMENS | Manufacturer Part Number: 5TT4123-0



Manufacturer	SIEMENS
MPN / Reference	5TT4123-0
Catalog number	41230
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-5DE54C384D
Generated	2026-08-02

Product Overview

Remote control switch with 3 NO contacts with central ON/OFF function Contact for 230 V AC, 400V 16A Control 230 V AC
Teleruptor with 3 NA contacts, with CENTRAL Connection/Disconnection function for 230/400V AC 16A, 230V AC control

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems
--------------	---

Additional Product Information

Technical data

Remote control switch with 3 NO contacts with central ON/OFF function Contact for 230 V AC, 400V 16A Control 230 V AC
Model

product brand name SENTRON

product designation Remote control switch

latching relay design mechanical for central control

General technical data

electrical endurance (switching cycles) 50 000

galvanic isolation / between magnet coil and contact Yes

switching voltage / of the contacts / at AC / minimum 10 V

switching current / at AC / per contact / minimum 100 mA

power loss [V•A] / of magnet coil / with pulse / rated value 7 VA

Voltage

type of voltage / of the operating voltage AC

continuous voltage fuse version PTC
operating range factor control supply voltage rated value / at AC / at 50 Hz
? initial value 0.8
? full-scale value 1.1
surge voltage resistance / rated value 4 kV
supply voltage 250 V
Supply voltage
supply voltage / minimum 250 V
Protection class
protection class IP IP20, with connected conductors
Switching capacity
switching capacity apparent power
? for fluorescent lamp load with DUO circuit 700 VA
? for fluorescent lamp load with parallel compensation 300 VA
? for uncompensated fluorescent lamp load 400 VA
switching capacity current
? at cos phi 0.6 16 A
? rated value 16 A
switching capacity active power / with incandescent lamp load 2 000 W
Dissipation
power loss [W]
? at 16 A / per contact / rated value 1.2 W
? of magnet coil / with pulse / rated value 4.5 W
switching current
? with glow lamp load / with 5TT4 920 compensa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT4123-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.