

INDUSTRIAL COMPONENT DATA

5TT4151-2 SIEMENS Remote control switch 1 NO Central and group switching Contact for 230 V AC, 400V 16A Cont..

Brand: SIEMENS | Manufacturer Part Number: 5TT4151-2



Manufacturer	SIEMENS
MPN / Reference	5TT4151-2
Catalog number	41512
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-3AB2510FCB
Generated	2026-08-05

Product Overview

Remote control switch 1 NO Central and group switching Contact for 230 V AC, 400V 16A Control 24 V AC
Teleswitch with 1 NA contacts, with centralized and grouped maneuver for 230/250V AC 16A, control at 24V AC.
Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems

Additional Product Information

Technical data

Remote control switch 1 NO Central and group switching Contact for 230 V AC, 400V 16A Control 24 V AC

Model

product brand name SENTRON

product designation Remote control switch

latching relay design Mechanical group switch

General technical data

electrical endurance (switching cycles) 50 000

galvanic isolation / between magnet coil and contact Yes

switching voltage / of the contacts / at AC / minimum 10 V

switching current / at AC / per contact / minimum 100 mA

power loss [V•A] / of magnet coil / with pulse / rated value 7 VA

Voltage

type of voltage / of the operating voltage AC
continuous voltage fuse version Yes
operating range factor control supply voltage rated value / at AC / at 50 Hz
? initial value 0.8
? full-scale value 1.1
surge voltage resistance / rated value 4 kV
supply voltage 250 V
Supply voltage
supply voltage / minimum 250 V
Protection class
protection class IP IP20, with connected conductors
Switching capacity
switching capacity apparent power
? for fluorescent lamp load with DUO circuit 700 VA
? for fluorescent lamp load with parallel compensation 300 VA
? for uncompensated fluorescent lamp load 400 VA
switching capacity current
? at cos phi 0.6 16 A
? rated value 16 A
switching capacity active power / with incandescent lamp load 2 000 W
Dissipation
power loss [W]
? at 16 A / per contact / rated value 1.2 W
? of magnet coil / with pulse / rated value 4.5 W
switching current
? with glow lamp load / with 5TT4 920 compensating capacitor 25 mA
?....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT4151-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.