


**INDUSTRIAL COMPONENT DATA**

# 5TT4456-2 SIEMENS Remote control switch Contact for 32 A Voltage 24 V AC 2 NO 2 NC

Brand: SIEMENS | Manufacturer Part Number: 5TT4456-2



|                 |                |
|-----------------|----------------|
| Manufacturer    | SIEMENS        |
| MPN / Reference | 5TT4456-2      |
| Catalog number  | 44562          |
| Category        | Latching relay |
| Minimum order   | 1 Pcs          |
| Document ID     | EO-A846BFF7EC  |
| Generated       | 2026-08-03     |

## Product Overview

Remote control switch Contact for 32 A Voltage 24 V AC 2 NO 2 NC

RELE BISTABLE CONTACT FOR 32 TO VOLTAGE AC 24 V 2 NA 2 NC. Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems**

## Additional Product Information

**Technical data**

Remote control switch Contact for 32 A Voltage 24 V AC 2 NO 2 NC

**Model**

product brand name SENTRON

product designation Remote control switch

latching relay design Mechanical switch

**General technical data**

electrical endurance (switching cycles) 50 000

galvanic isolation / between magnet coil and contact Yes

switching voltage / of the contacts / at AC / minimum 10 V

switching current / at AC / per contact / minimum 100 mA

power loss [V•A] / of magnet coil / with pulse / rated value 18 VA

**Voltage**

type of voltage / of the operating voltage AC  
continuous voltage fuse version Yes  
surge voltage resistance / rated value 3 kV  
supply voltage 400 V  
Supply voltage  
supply voltage / minimum 230 V  
Protection class  
protection class IP IP20  
Switching capacity  
switching capacity apparent power  
? for fluorescent lamp load with DUO circuit 2 436 VA  
? for fluorescent lamp load with parallel compensation 1 218 VA  
? for uncompensated fluorescent lamp load 2 204 VA  
switching capacity current  
? at cos phi 0.6 32 A  
? rated value 32 A  
switching capacity active power / with incandescent lamp load 7 000 W  
Dissipation  
power loss [W]  
? at 16 A / per contact / rated value 3 W  
? of magnet coil / with pulse / rated value 13 W  
Control current  
type of voltage  
? of control voltage\_1 AC  
control voltage  
? \_1 / initial value 207 V  
? \_1 / full-scale value 253 V  
? \_1 / setpoint 24 V  
control voltage frequency  
? \_1 / initial value 50 Hz  
? \_1 / full-scale value 60 Hz  
Product details  
product component / sw...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT4456-2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.