

**INDUSTRIAL COMPONENT DATA**

# 5TT5031-2 SIEMENS INSTA contactor with 3 NO contacts and 1 NC Contact for 230 V AC, 400V 25A Control AC/24 V..

Brand: SIEMENS | Manufacturer Part Number: 5TT5031-2



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | SIEMENS                                       |
| MPN / Reference | 5TT5031-2                                     |
| Catalog number  | 50312                                         |
| Category        | Installation contactor for distribution board |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-C48364132E                                 |
| Generated       | 2026-08-06                                    |

## Product Overview

INSTA contactor with 3 NO contacts and 1 NC Contact for 230 V AC, 400V 25A Control AC/24 V DC  
 INSTALLATION CONTACTOR WITH 3 NA CONT. AND 1 NC CONT. FOR AC 230, 400V 25A COMMAND TO ACDC24V.  
 Cancellations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems |
|--------------|---------------------------------------------------------------------------------|

## Additional Product Information

**Technical data**

INSTA contactor with 3 NO contacts and 1 NC Contact for 230 V AC, 400V 25A Control AC/24 V DC

**Model**

product brand name SENTRON

product designation Insta contactor

design of the product 3 NO contacts 1 NC contact

type of voltage / of the operating voltage AC

type of voltage / of the operating voltage / for actuation AC/DC

Supply voltage

operating voltage / rated value

? minimum 400 V

? maximum 400 V

Protection class

protection class IP IP20

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 2.2 W

Current

operational current / at AC / rated value 25 A

Control current

control supply voltage

? rated value 24 V

? rated value / maximum 24 V

? at DC / rated value 24 V

Product details

product component / slide for manual operation No

number of NC contacts 1

number of NO contacts 3

product extension / installable / supplementary devices Yes

Mechanical Design

height 90 mm

width 35 mm

depth 71 mm

installation depth 64 mm

number of modular width units 2

net weight 150 g

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmation

Miscellaneous

Declaration of Conformity Test Certificates other

UK Declaration of Conformity

Special Test Certificate

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT50...>

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT5031-2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](http://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.