

**INDUSTRIAL COMPONENT DATA**

# 5TT6112 SIEMENS overcurrent relay T5570 230V AC 10A 1-phase with transparent cap

Brand: SIEMENS | Manufacturer Part Number: 5TT6112



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | SIEMENS                  |
| MPN / Reference | 5TT6112                  |
| Catalog number  | 10000                    |
| Category        | Current monitoring relay |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-ED8E9F6C1E            |
| Generated       | 2026-08-02               |

## Product Overview

overcurrent relay T5570 230V AC 10A 1-phase with transparent cap

Current relay &gt;N

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems |
|--------------|---------------------------------------------------------------------------------|

## Additional Product Information

Technical data

overcurrent relay T5570 230V AC 10A 1-phase with transparent cap

Model

product brand name SENTRON

product designation Undercurrent relay

design of the product Undercurrent relay

General technical data

adjustable pickup delay time / initial value 0.1 s

type of voltage / of the operating voltage / for actuation AC

Current

measurable current / at AC

? initial value 10 A

? full-scale value 10 A

Control current

control supply voltage / at AC

? at 50 Hz / rated value / minimum 230 V

? at 50 Hz / rated value / maximum 230 V

? at 60 Hz / rated value / minimum 230 V

? at 60 Hz / rated value / maximum 230 V

Auxiliary circuit

number of CO contacts / for auxiliary contacts 1

number of NC contacts / for auxiliary contacts 0

number of NO contacts / for auxiliary contacts 0

Adjustable parameters

adjustable pickup delay time / full-scale value 20 s

adjustable OFF-delay time

? initial value 0.1 s

? full-scale value 20 s

Product function

product function

? voltage window recognition 1 phase No

? voltage window recognition 3 phase No

? current window recognition DC No

? overcurrent detection 1 phase Yes

? overcurrent detection 3 phase No

? overcurrent detection DC No

? undercurrent detection 1 phase No

? undercurrent detection 3 phases No

? undercurrent detection DC No

Connections

type of electrical connection screw-type terminals

? plug-in socket No

Mechanical Design

height 90 mm

width 18 mm

depth 64 mm

net weight 81 g

Downloads and manuals

General Product Approval Declaration....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT6112 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.