

INDUSTRIAL COMPONENT DATA

5TT6114 SIEMENS overcurrent relay T5570 230V AC 1/5/10/15A 1-phase with transparent cap

Brand: SIEMENS | Manufacturer Part Number: 5TT6114



Manufacturer	SIEMENS
MPN / Reference	5TT6114
Catalog number	10000
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-D7BB764340
Generated	2026-08-01

Product Overview

overcurrent relay T5570 230V AC 1/5/10/15A 1-phase with transparent cap

Current relay >N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Other Modular Systems

Additional Product Information

Technical data

overcurrent relay T5570 230V AC 1/5/10/15A 1-phase with transparent cap

Model

product brand name SENTRON

product designation Undercurrent relay

design of the product Undercurrent relay

General technical data

adjustable pickup delay time / initial value 0.1 s

type of voltage / of the operating voltage / for actuation AC

Current

measurable current / at AC

? initial value 15 A

? full-scale value 15 A

Control current

control supply voltage / at AC

? at 50 Hz / rated value / minimum 230 V

? at 50 Hz / rated value / maximum 230 V

? at 60 Hz / rated value / minimum 230 V

? at 60 Hz / rated value / maximum 230 V

Auxiliary circuit

number of CO contacts / for auxiliary contacts 2

number of NC contacts / for auxiliary contacts 0

number of NO contacts / for auxiliary contacts 0

Adjustable parameters

adjustable pickup delay time / full-scale value 20 s

adjustable OFF-delay time

? initial value 0.1 s

? full-scale value 20 s

Product function

product function

? voltage window recognition 1 phase No

? voltage window recognition 3 phase No

? current window recognition DC No

? overcurrent detection 1 phase Yes

? overcurrent detection 3 phase No

? overcurrent detection DC No

? undercurrent detection 1 phase No

? undercurrent detection 3 phases No

? undercurrent detection DC No

Connections

type of electrical connection screw-type terminals

? plug-in socket No

Mechanical Design

height 90 mm

width 36 mm

depth 64 mm

net weight 149 g

Downloads and manuals

General Product Approval Decl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 5TT6114 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.