

INDUSTRIAL COMPONENT DATA

6SL3210-1KE32-4AF1 SIEMENS SINAMICS G120C RATED POWER 132.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-1KE32-4AF1



Manufacturer	SIEMENS
MPN / Reference	6SL3210-1KE32-4AF1
Catalog number	32101
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-91169B1E86
Generated	2026-08-06

Product Overview

SINAMICS G120C RATED POWER 132.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSF 708x 305x 357(HXW XD) EXTERNAL 24V SINAMICS G120C ASSIGNED POWER 132.0KW WITH 150% OVERCHARGE BY 3 SEC 3AC380-480V +10/-20% 47-63HZ FILTER CL. A INTEGRATED I/O INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN; DEGREE OF PROTECTION IP20/ UL OPEN TYPE SIZE: FSF 708x 305x 357(AXXP) 24V EXTERNAL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > DRIVES > SINAMICSG120C**

Additional Product Information

Technical data

SINAMICS G120C RATED POWER 132.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSF 708x 305x 357(HXW XD) EXTERNAL 24V

Downloads and manuals
Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,

...)https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)https://mall.industry.siemens.com

Date

5/5/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3210-1KE32-4AF1

Product Description SINAMICS G120C RATED POWER 132.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V
+10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF
INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSF 708x 305x 357(HXWxD)
EXTERNAL 24V

Product family SINAMICS G120C compact converters

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 340 / 340

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL : N / ECCN : EAR99H

Standard lead time ex-works 30 Day/Days

Net Weight (kg) 66,000 Kg

Packaging Dimension 469,00 x 745,00 x 385,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-1KE32-4AF1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.