

INDUSTRIAL COMPONENT DATA

6SL3210-1PB21-8AL0 SIEMENS SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CH..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-1PB21-8AL0



Manufacturer	SIEMENS
MPN / Reference	6SL3210-1PB21-8AL0
Catalog number	32101
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-978C1D7583
Generated	2026-08-04

Product Overview

SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 1/3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -10 TO +40 DEG C 355 X 140 X 165 (HXWXD), FSC PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > DRIVES > SINAMICS G120 Power Modules Size A**

Additional Product Information

Technical data

SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 1/3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -10 TO +40 DEG C 355 X 140 X 165 (HXWXD), FSC PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.6

[Downloads and manuals](#)
[Further information](#)
[Industry Online Support \(Manuals, Catalogs, Certificates, FAQ,](#)

...)https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)https://mall.industry.siemens.com

Date

5/11/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3210-1PB21-8AL0

Product Description SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 1/3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -10 TO +40 DEG C 355 X 140 X 165 (HXWXD), FSC PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.6

Product family Power Modules

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 338 / 338

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL :....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-1PB21-8AL0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.