

**INDUSTRIAL COMPONENT DATA**

# 6SL3210-1PE16-1AL1 SIEMENS SINAMICS Power Module PM240-2 with integrated Class A filter with integrated brak..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-1PE16-1AL1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | SIEMENS                            |
| MPN / Reference | 6SL3210-1PE16-1AL1                 |
| Catalog number  | 32101                              |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-828C0E17AB                      |
| Generated       | 2026-08-04                         |

## Product Overview

SINAMICS Power Module PM240-2 with integrated Class A filter with integrated braking chopper 380-480 V 3 AC +10/-10% 47-63 Hz Power high overload: 1.5kW at 200% 3s, 150% 57s, 100% 240 s; Ambient temperature -10 to +50 °C; power low overload: 2.2kW at 150% 3s, 110% 57s, 100% 240 s; Ambient temperature -10 to +40 °C 196x 73x 165 (HxWxD), FSA Degree of protection IP20 without Control Unit and operating unit Released as of CU firmware version V4.6

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > DRIVES > SINAMICS G120 Power Modules Size A**

## Additional Product Information

**Technical data**

SINAMICS Power Module PM240-2 with integrated Class A filter with integrated braking chopper 380-480 V 3 AC +10/-10% 47-63 Hz Power high overload: 1.5kW at 200% 3s, 150% 57s, 100% 240 s; Ambient temperature -10 to +50 °C; power low overload: 2.2kW at 150% 3s, 110% 57s, 100% 240 s; Ambient temperature -10 to +40 °C 196x 73x 165 (HxWxD), FSA Degree of protection IP20 without Control Unit and operating unit Released as of CU firmware version V4.6

**Downloads and manuals**
**Further information**

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,  
[...](https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW)<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)<https://mall.industry.siemens.com>

**Date**

5/13/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3210-1PE16-1AL1

Product Description SINAMICS Power Module PM240-2 with integrated Class A filter with integrated braking chopper  
380-480 V 3 AC +10/-10% 47-63 Hz Power high overload: 1.5kW at 200% 3s, 150% 57s, 100% 240 s; Ambient temperature  
-10 to +50 °C; power low overload: 2.2kW at 150% 3s, 110% 57s, 100% 240 s; Ambient temperature -10 to +40 °C 196x  
73x 165 (HxWxD), FSA Degree of protection IP20 without Control Unit and operating unit Released as of CU firmware  
version V4.6

Product family Power Modules

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 338 / 338

Surcharge for Raw Ma...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-1PE16-1AL1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.