

INDUSTRIAL COMPONENT DATA

6SL3210-1PE28-8UL0 SIEMENS SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-1PE28-8UL0



Manufacturer	SIEMENS
MPN / Reference	6SL3210-1PE28-8UL0
Catalog number	32101
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-C63B0BC78A
Generated	2026-08-05

Product Overview

SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 551 X 275 X 237 (HXWXD), FSE PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 HF8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > DRIVES > SINAMICS G120 Power Modules Size A
--------------	---

Additional Product Information

Technical data

SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 551 X 275 X 237 (HXWXD), FSE PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 HF8

Downloads and manuals

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,

...)https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)https://mall.industry.siemens.com

Date

5/9/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3210-1PE28-8UL0

Product Description SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING
CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S
AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45KW FOR 150% 3S,110% 57S,100% 240S
AMBIENT TEMP -20 TO +40 DEG C (LO) 551 X 275 X 237 (HXWXD), FSE PROTECTION IP20 WITHOUT CONTROL
UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 HF8

Product family Power Modules

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 339 / 339

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-1PE28-8UL0 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.