

INDUSTRIAL COMPONENT DATA

**6SL3210-5BB11-2BV1 SIEMENS SINAMICS V20 200-240V 1AC
-10/+10% 47-63Hz rated power 0.12 kW with 150% overload..**

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-5BB11-2BV1



Manufacturer	SIEMENS
MPN / Reference	6SL3210-5BB11-2BV1
Catalog number	32105
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-025D775AB7
Generated	2026-08-06

Product Overview

SINAMICS V20 200-240V 1AC -10/+10% 47-63Hz rated power 0.12 kW with 150% overload for 60 sec. integrated filter C1
I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: AA 68x142x108
(WxHxD)

SINAMICS V20 1AC 200-240V -10/+10% 47-63Hz, Nominal power 0.12 KW with 150% overload for 60 seconds, WITH
integrated C1 FILTER. I/O INTERFACE: 4DI, 2ND, 2AI, 1AO. Fieldbus: USS/MODBUS RTU with built-in BOP. DEGREE
OF PROTECTION: IP20 / UL or. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > DRIVES > SINAMICS V20 and G110 with Macros and Communications 22 / 30kW
--------------	---

Additional Product Information

Technical data

SINAMICS V20 200-240V 1AC -10/+10% 47-63Hz rated power 0.12 kW with 150% overload for 60 sec. integrated filter C1
I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: AA 68x142x108
(WxHxD)

Downloads and manuals

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,
...) <https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system) <https://mall.industry.siemens.com>

Date

5/15/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3210-5BB11-2BV1

Product Description SINAMICS V20 200-240V 1AC -10/+10% 47-63Hz rated power 0.12 kW with 150% overload for 60 sec. integrated filter C1 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: AA 68x142x108 (WxHxD)

Product family SINAMICS V20 basic converters

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 350 / 350

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 40 Day/Days

Net Weight (kg) 0,700 Kg

Packaging Dimension 205,00 x 180,00 x 140,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4042948669778

UPC 804766253317

Commodity Code 85044084

LKZ_FDB/ CatalogID SINAMICS V2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-5BB11-2BV1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.