

## INDUSTRIAL COMPONENT DATA

**6SL3210-5BE17-5CV0 SIEMENS SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 0.75 kW with 150% overlo..**

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-5BE17-5CV0



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | SIEMENS                            |
| MPN / Reference | 6SL3210-5BE17-5CV0                 |
| Catalog number  | 6SL3210-5BE17-5CV0                 |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 unit                             |
| Document ID     | EO-49FC00B700                      |
| Generated       | 2026-08-06                         |

**Product Overview**

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 0.75 kW with 150% overload for 60 sec. Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: A 90x150x146 (WxHxD)

SINAMICS V20 3AC 380-480V -15 / +10% 47-63HZ, Rated power 0.75 kW with 150% overload for 60 seconds WITH integrated FILTER C3, I/O INTERFACE: 4DI, 2ND, 2AI, 1AO, Fieldbus: USS / MODBUS RTU with built-in BOP, DEGREE OF PROTECTION: IP20 / UL open type, SIZE: FSA 90X150X146 (H x W x D). Manufactured to order. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path SIEMENS > DRIVES > SINAMICS V20 and G110 with Macros and Communications 22 / 30kW

**Additional Product Information**

## Technical data

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 0.75 kW with 150% overload for 60 sec. Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: A 90x150x146 (WxHxD)

## Downloads and manuals

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,  
...) <https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>  
Industry Mall (Online ordering system) <https://mall.industry.siemens.com>

**Date**

5/5/2022 Subject to change without notice

© Copyright Siemens 2022

**Additional data****Product**

Article Number (Market Facing Number) 6SL3210-5BE17-5CV0

Product Description SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 0.75 kW with 150% overload for 60 sec. Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: A 90x150x146 (WxHxD)

Product family SINAMICS V20 basic converters

Product Lifecycle (PLM) PM300:Active Product

**Price data**

Region Specific PriceGroup / Headquarter Price Group 350 / 350

Surcharge for Raw Materials None

Metal Factor None

**Delivery information**

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 40 Day/Days

Net Weight (kg) 0,990 Kg

Packaging Dimension 180,00 x 220,00 x 140,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

**Additional Product Information**

EAN 6940408102620

UPC 887621057763

Commodity Code 85044084

LKZ\_FDB/ CatalogID SINAMICS V...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 6SL3210-5BE17-5CV0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.