

INDUSTRIAL COMPONENT DATA

6SL3210-5BE25-5CV0 SIEMENS SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 5.5 kW with 150% overloa..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-5BE25-5CV0



Manufacturer	SIEMENS
MPN / Reference	6SL3210-5BE25-5CV0
Catalog number	32105
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-D524F11203
Generated	2026-08-06

Product Overview

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 5.5 kW with 150% overload for 60 sec. Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: C 184x182x169 (WxHxD)

SINAMICS V20 3AC 380-480V -15 / +10% 47-63HZ, Rated power 5.5 kW with 150% overload for 60 seconds WITH integrated filter C3, I/O INTERFACE: 4DI, 2ND, 2AI, 1AO, Fieldbus: USS / MODBUS RTU with built-in BOP, DEGREE OF PROTECTION: IP20 / UL open type, SIZE: FSC 184X182X169 (H x W x D). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > DRIVES > SINAMICS V20 and G110 with Macros and Communications 22 / 30kW**

Additional Product Information

Technical data

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 5.5 kW with 150% overload for 60 sec. Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: C 184x182x169 (WxHxD)

Downloads and manuals
Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

Date

5/11/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data**Product**

Article Number (Market Facing Number) 6SL3210-5BE25-5CV0

Product Description SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 5.5 kW with 150% overload for 60 sec.

Integrated filter C3 I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: C 184x182x169 (WxHxD)

Product family SINAMICS V20 basic converters

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 350 / 350

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 40 Day/Days

Net Weight (kg) 2,600 Kg

Packaging Dimension 237,00 x 220,00 x 247,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 6940408102682

UPC 887621057893

Commodity Code 85044084

LKZ_FDB/ CatalogID SINAMICS....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3210-5BE25-5CV0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.