

INDUSTRIAL COMPONENT DATA

6SL3210-5BE31-8UV0 SIEMENS SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 18.5 kW with 150% overlo..

Brand: SIEMENS | Manufacturer Part Number: 6SL3210-5BE31-8UV0



Manufacturer	SIEMENS
MPN / Reference	6SL3210-5BE31-8UV0
Catalog number	32105
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-04CB9817AC
Generated	2026-08-06

Product Overview

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 18.5 kW with 150% overload for 60 sec. small output overload: 22 kW with 110% overload for 60 sec. unfiltered I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: E 244x265x209 (WxHxD)

SINAMICS V20 3AC 380-480V -15/+10% 47-63HZ. High overload power: 18,5KW with 150% overload for 60seconds. Low overload power: 22KW with 110% overload for 60 seconds, without filter. I/O-interface: 4DI, 2DO, 2AI, 1AO fieldbus: USS/MODBUS RTU with built-in BOP, degree of protection: IP20/ UL OPEN type. Size: FSE 264.5x243.5x209 (H x W x D). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > DRIVES > SINAMICS V20 and G110 with Macros and Communications 22 / 30kW
--------------	---

Additional Product Information

Technical data

SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 18.5 kW with 150% overload for 60 sec. small output overload: 22 kW with 110% overload for 60 sec. unfiltered I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus: USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: E 244x265x209 (WxHxD)

Downloads and manuals

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,
...) <https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system) <https://mall.industry.siemens.com>

Date

5/15/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data**Product**

Article Number (Market Facing Number) 6SL3210-5BE31-8UV0

Product Description SINAMICS V20 380-480 V 3 AC -15/+10% 47-63Hz rated power 18.5 kW with 150% overload for 60 sec. small output overload: 22 kW with 110% overload for 60 sec. unfiltered I/O: 4 DI, 2 DO, 2 AI, 1 AQ fieldbus:

USS/MODBUS RTU with built-in BOP protection: IP20/ UL open size: E 244x265x209 (WxHxD)

Product family SINAMICS V20 basic converters

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 350 / 350

Surcharge for Raw Materials None

Metal Factor None

Delivery information

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 40 Day/Days

Net Weight (kg) 6,240 Kg

Packaging Dimension 320,00 x 340,00 x 280,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Produ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend SIEMENS / 6SL3210-5BE31-8UV0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.