

INDUSTRIAL COMPONENT DATA

6SL3211-1PC31-8UL0 SIEMENS SINAMICS G120 POWER MODULE PM240-2 Push Through, UNFILTERED WITH BUILT IN BRAKING..

Brand: SIEMENS | Manufacturer Part Number: 6SL3211-1PC31-8UL0



Manufacturer	SIEMENS
MPN / Reference	6SL3211-1PC31-8UL0
Catalog number	10000
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-FC3F924E6A
Generated	2026-08-05

Product Overview

SINAMICS G120 POWER MODULE PM240-2 Push Through, UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 754x384x358 (HXWXD), FSF PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

SINAMICS G120 POWER MODULE PM240-2 Push Through, WITHOUT FILTER WITH INTEGRATED CHOPPER BRAKE 3AC200-240V +10/-20% 47-63HZ POTENC. HIGH OVERLOAD: 45KW WITH 200% 3S,150% 57S,100% 240S TEMP. AMBI. -20 A +50 GRD C (HO) POTEN. LOW OVERLOAD: 55kW WITH 150% 3S,110% 57S,100% 240S TEMP. AMBI. -20 BIS +40 GRD C (LO) 754x384x358 (ALXAXP), FSF PROTECTION GRADE IP20 WITHOUT CONTROL UNIT AND CONTROL UNIT APPROVED FROM CU FIRMWARE- VERSION V4.7 SP6. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > DRIVES > SINAMICS G120 Power Modules Size A**

Additional Product Information

Technical data

SINAMICS G120 POWER MODULE PM240-2 Push Through, UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT

TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 754x384x358 (HXWxD), FSF PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

Downloads and manuals

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

Date

5/11/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3211-1PC31-8UL0

Product Description SINAMICS G120 POWER MODULE PM240-2 Push Through, UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 754x384x358 (HXWxD), FSF PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

Product family Power Modules

Product Lifecycle (PLM) PM400:Phase Out Started

PLM Effective Date Product phase-out since: 01.10.2021

Price data

Region Specific PriceGroup / Headquarter Price Group 339 / 339

Surcharge for Raw Ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3211-1PC31-8UL0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.