

INDUSTRIAL COMPONENT DATA

6SL3211-1PE27-5AL0 SIEMENS SINAMICS G120 POWER MODULE PM240-2 Push Through, WITH BUILT IN CL. A FILTER WITH ..

Brand: SIEMENS | Manufacturer Part Number: 6SL3211-1PE27-5AL0



Manufacturer	SIEMENS
MPN / Reference	6SL3211-1PE27-5AL0
Catalog number	10000
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E9533EB29E
Generated	2026-08-05

Product Overview

SINAMICS G120 POWER MODULE PM240-2 Push Through, WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 517x275x237 (HXWXD), FSD PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

SINAMICS G120 POWER MODULE PM240-2 Push Through, CL FILTER. A INTEGRATED WITH INTEGRATED CHOPPER BRAKE 3AC380-480V +10/-20% 47-63HZ POTENC. HIGH OVERLOAD: 30KW WITH 200% 3S,150% 57S,100% 240S TEMP. AMBI. -20 A +50 GRD C (HO) POTEN. LOW OVERLOAD: 37kW WITH 150% 3S,110% 57S,100% 240S TEMP. AMBI. -20 BIS +40 GRD C (LO) 517x275x237 (ALXAXP), FSD PROTECTION GRADE IP20 WITHOUT CONTROL UNIT AND CONTROL UNIT APPROVED FROM CU FIRMWARE- VERSION V4.7 SP6. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > DRIVES > SINAMICS G120 Power Modules Size A

Additional Product Information

Technical data

SINAMICS G120 POWER MODULE PM240-2 Push Through, WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S

AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37kW FOR 150% 3S,110% 57S,100% 240S
AMBIENT TEMP -20 TO +40 DEG C (LO) 517x275x237 (HXWxD), FSD PROTECTION IP20 WITHOUT CONTROL UNIT
AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

Downloads and manuals

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ,
...) <https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system) <https://mall.industry.siemens.com>

Date

5/12/2022 Subject to change without notice

© Copyright Siemens 2022

Additional data

Product

Article Number (Market Facing Number) 6SL3211-1PE27-5AL0

Product Description SINAMICS G120 POWER MODULE PM240-2 Push Through, WITH BUILT IN CL. A FILTER WITH
BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200%
3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37kW FOR 150%
3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 517x275x237 (HXWxD), FSD PROTECTION IP20
WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6

Product family Power Modules

Product Lifecycle (PLM) PM400:Phase Out Started

PLM Effective Date Product phase-out since: 01.10.2021

Price data

Region Specific PriceGroup / Headquarter Price Grou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 6SL3211-1PE27-5AL0 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.