

INDUSTRIAL COMPONENT DATA

7KM5212-6BA00-1EA2 SIEMENS SENTRON, measuring device, 7KM PAC5100, LCD, L-L: 690 V, L-N: 400 V, 10 A, 3-phas..

Brand: SIEMENS | Manufacturer Part Number: 7KM5212-6BA00-1EA2



Manufacturer	SIEMENS
MPN / Reference	7KM5212-6BA00-1EA2
Catalog number	52126
Category	Multifunction measuring instrument
Minimum order	1 Pcs
Document ID	EO-6CD4D49D97
Generated	2026-08-05

Product Overview

SENTRON, measuring device, 7KM PAC5100, LCD, L-L: 690 V, L-N: 400 V, 10 A, 3-phase, Modbus TCP, apparent/active/reactive energy / cos phi, harmonics: 2. - 40., THD, class 0.5 acc to IEC61557- 12 or cl. 0.5S acc. to IEC62053-22, wide-range pwr sup. unit AC/DC, screw terminals

SENTRON PAC5100, LCD, 96X96MM POWER MONITORING DEVICE PANEL INSTRUMENT TO MEASURE ELECTRICAL VARIABLES PROTOCOL: MODBUS TCP WITH GRAPHIC DISPLAY. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SENTRON PAC network analyzers. E

Additional Product Information

Technical data

SENTRON, measuring device, 7KM PAC5100, LCD, L-L: 690 V, L-N: 400 V, 10 A, 3-phase, Modbus TCP, apparent/active/reactive energy / cos phi, harmonics: 2. - 40., THD, class 0.5 acc to IEC61557- 12 or cl. 0.5S acc. to IEC62053-22, wide-range pwr sup. unit AC/DC, screw terminals

Model

product brand name SENTRON

product designation 7KM PAC5100

design of the product compact

product type designation Measuring instrument
Measurements
measuring procedure
? for voltage measurement TRMS
? for current measurement TRMS
type of measured value detection complete
voltage curve Sinusoidal or distorted
measurable line frequency
? initial value 45 Hz
? full-scale value 65 Hz
operating mode for measured value detection automatic line frequency detection Yes
operating mode for measured value detection
? set at 50 Hz No
? set to 60 Hz No
Supply voltage
design of the power supply Wide-range power supply
type of voltage of the supply voltage AC/DC
Degree of protection protection class
protection class IP on the front IP40
operating resource protection class when installed safety class II
Suitability
suitability for operation Installation in stationary control panels in closed rooms
Product Functions
product function
? voltage measurement Yes
? current measurement Yes
? active power measurement Yes
? reactive power measurement Yes
? frequency measurement Yes
Display and operation
design of the display LCD
height of the display 54 mm
width of the display 72 mm
color of the background....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 7KM5212-6BA00-1EA2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.