

INDUSTRIAL COMPONENT DATA

7KM9300-0AE01-0AA0 SIEMENS expansion module switched Ethernet PROFINET, plug-in, for 7KM PAC3200 / 4200 / 3V..

Brand: SIEMENS | Manufacturer Part Number: 7KM9300-0AE01-0AA0



Manufacturer	SIEMENS
MPN / Reference	7KM9300-0AE01-0AA0
Catalog number	93000
Category	Multifunction measuring instrument
Minimum order	1 Pcs
Document ID	EO-8D7F5A8DBF
Generated	2026-08-02

Product Overview

expansion module switched Ethernet PROFINET, plug-in, for 7KM PAC3200 / 4200 / 3VA COM100 / 800

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SENTRON PAC network analyzers. E

Additional Product Information

ETIM: EC002301 - Multifunction measuring instrument

Value Unit

Ampere meter (EF006555) false

Blind power meter (EF006556) false

With rotational speed meter (EF006557) false

Frequency meter (EF006558) false

Pulse counter (EF006559) false

Voltmeter (EF006560) false

Effective power measurement device (EF006561) false

expansion module switched Ethernet PROFINET, plug-in, for 7KM PAC3200 / 4200 / 3VA COM100 / 800

Model

product brand name SENTRON

Product designation Switched Ethernet PROFINET expansion module

General technical data

MTBF 215.6 y

Galvanic isolation Maximum insulation voltage: 500V AC

Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750 P

Degree of pollution 2 according to IEC 61131

Protection class

Protection class IP IP20

Combustibility class acc. to UL 94 V 0

Communication

Protocol / is supported PROFINET IO / Modbus TCP

Transfer rate

? minimum 10 000 kbit/s

? maximum 100 000 kbit/s

Connections

type of electrical connection 2 x RJ45 socket

Mechanical Design

Height 63 mm

Width 43 mm

Depth 22 mm

Mounting type pluggable

Environmental conditions

Ambient temperature / during operation

? minimum -5 °C

? maximum 55 °C

Ambient temperature / during storage

? minimum -25 °C

? maximum 70 °C

Certificates

? Certificate of suitability / as EC declaration of conformity IEC 61010-1: 2001 (2nd Ed.) with Corr. 1, EN 61010-1: 2001 (2nd Ed.) and DIN EN 61010-1:2002 with "Berichtigung 1"

? Certificate of suitability / as approval for USA IEC 61010-1: 20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 7KM9300-0AE01-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.