

INDUSTRIAL COMPONENT DATA

8MR2110-0B SIEMENS Semiconductor heater, small, HGK 047 110-250 V, 10 W

Brand: SIEMENS | Manufacturer Part Number: 8MR2110-0B



Manufacturer	SIEMENS
MPN / Reference	8MR2110-0B
Catalog number	21100
Category	Heating (switchgear cabinet)
Minimum order	3 Pcs
Document ID	EO-5628038A24
Generated	2026-08-03

Product Overview

Semiconductor heater, small, HGK 047 110-250 V, 10 W

INTERNAL CONVECTION HEATING DEVICE FOR DISTRIBUTION AND CONTROL CABINET, NOMINAL POWER 10W (** ATTENTION: Price per 1 Unit and Minimum Quantity / Order Multiple 3 Units **). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON

Additional Product Information

Technical data

Semiconductor heater, small, HGK 047 110-250 V, 10 W

Model

product brand name SIVACON

product designation heater unit

design of the product Small semiconductor

General technical data

operating temperature

? minimum -45 °C

? maximum 70 °C

Voltage

type of voltage / of the operating voltage AC/DC

continuous heating power / at 20 °C 10 W

inrush current / typical 1 A

operating voltage

? rated value / minimum 240 V

? rated value / maximum 240 V

? at AC / at 50 Hz / rated value / minimum 110 V

? at AC / at 50 Hz / rated value / maximum 250 V

? at AC / at 60 Hz / rated value / minimum 110 V

? at AC / at 60 Hz / rated value / maximum 250 V

? at DC / rated value / minimum 110 V

? at DC / rated value / maximum 250 V

Protection class

protection class IP IP44

Main circuit

operational current / of the slow-blow fuse link 1 A

Product details

product component

? blower No

? thermostat No

Connections

type of connection technology 3 x 0.5 mm² x 300 mm line (silicon)

Mechanical Design

height 50 mm

width 50 mm

depth 25 mm

fastening method Clip for 35 mm DIN rail

net weight 0.1 kg

material / of the enclosure aluminum

Environmental conditions

relative humidity / reference value 90 %

ambient temperature / during storage

? minimum -45 °C

? maximum 70 °C

Certificates

reference code / according to EN 61346-2 R

Downloads and manuals

General Product Approval Declaration of Conformity other
Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR2110-0B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.