

INDUSTRIAL COMPONENT DATA

8MR2110-0C SIEMENS Heater 110-120V, 10W UL-APP. HGK 047-04700.9-00

Brand: SIEMENS | Manufacturer Part Number: 8MR2110-0C



Manufacturer	SIEMENS
MPN / Reference	8MR2110-0C
Catalog number	21100
Category	Heating (switchgear cabinet)
Minimum order	3 Pcs
Document ID	EO-48FAD85BD2
Generated	2026-08-06

Product Overview

Heater 110-120V, 10W; UL-APP. HGK 047-04700.9-00

HEATER 110-120V,10W; UL-APP. HGK 047-04700.9-00 (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 3 Units **). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON

Additional Product Information

Technical data

Heater 110-120V, 10W; UL-APP. HGK 047-04700.9-00

Model

product brand name SIVACON

product designation heater unit

design of the product Small semiconductor

General technical data

operating temperature

? minimum -45 °C

? maximum 70 °C

Voltage

type of voltage / of the operating voltage AC/DC

continuous heating power / at 20 °C 10 W

inrush current / typical 1 A

operating voltage

? rated value / minimum 120 V

? rated value / maximum 120 V

? at AC / at 50 Hz / rated value / minimum 110 V

? at AC / at 50 Hz / rated value / maximum 120 V

? at AC / at 60 Hz / rated value / minimum 110 V

? at AC / at 60 Hz / rated value / maximum 120 V

? at DC / rated value / minimum 110 V

? at DC / rated value / maximum 120 V

Protection class

protection class IP IP44

Main circuit

operational current / of the slow-blow fuse link 1 A

Product details

product component

? blower No

? thermostat No

Connections

type of connection technology 3 x AWG 20 x 300 mm line

Mechanical Design

height 52 mm

width 50 mm

depth 25 mm

fastening method Clip for 35 mm DIN rail

net weight 0.1 kg

material / of the enclosure aluminum

Environmental conditions

relative humidity / reference value 90 %

ambient temperature / during storage

? minimum -45 °C

? maximum 70 °C

Certificates

reference code / according to EN 61346-2 R

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.s...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR2110-0C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.