

INDUSTRIAL COMPONENT DATA

8MR2110-2B SIEMENS Semiconductor heater, small, HGK 047 110-250 V, 20 W

Brand: SIEMENS | Manufacturer Part Number: 8MR2110-2B



Manufacturer	SIEMENS
MPN / Reference	8MR2110-2B
Catalog number	21102
Category	Heating (switchgear cabinet)
Minimum order	3 Pcs
Document ID	EO-47ABC4E535
Generated	2026-08-03

Product Overview

Semiconductor heater, small, HGK 047 110-250 V, 20 W

INTERNAL CONVECTION HEATING DEVICE FOR DISTRIBUTION AND CONTROL CABINET, NOMINAL POWER 20W (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 3 Units **). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON

Additional Product Information

Technical data

Semiconductor heater, small, HGK 047 110-250 V, 20 W

Model

product brand name SIVACON

product designation heater unit

design of the product Small semiconductor

General technical data

operating temperature

? minimum -45 °C

? maximum 70 °C

Voltage

type of voltage / of the operating voltage AC/DC

continuous heating power / at 20 °C 20 W

inrush current / typical 2.5 A

operating voltage

? rated value / minimum 240 V

? rated value / maximum 240 V

? at AC / at 50 Hz / rated value / minimum 110 V

? at AC / at 50 Hz / rated value / maximum 265 V

? at AC / at 60 Hz / rated value / minimum 110 V

? at AC / at 60 Hz / rated value / maximum 250 V

? at DC / rated value / minimum 110 V

? at DC / rated value / maximum 250 V

Protection class

protection class IP IP44

Main circuit

operational current / of the slow-blow fuse link 2 A

Product details

product component

? blower No

? thermostat No

Connections

type of connection technology 3 x 0.5 mm² x 300 mm line (silicon)

Mechanical Design

height 60 mm

width 50 mm

depth 25 mm

fastening method Clip for 35 mm DIN rail

net weight 0.2 kg

Environmental conditions

relative humidity / reference value 90 %

ambient temperature / during storage

? minimum -45 °C

? maximum 70 °C

Certificates

reference code / according to EN 61346-2 R

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltag...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR2110-2B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.