

INDUSTRIAL COMPONENT DATA

8MR2130-4BA SIEMENS Semiconductor Heater HG140 12-30 V AC/DC, 45 W

Brand: SIEMENS | Manufacturer Part Number: 8MR2130-4BA



Manufacturer	SIEMENS
MPN / Reference	8MR2130-4BA
Catalog number	21304
Category	Heating (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-E817282DB2
Generated	2026-08-05

Product Overview

Semiconductor Heater HG140 12-30 V AC/DC, 45 W

SEMICONDUCTOR HEATER HG140 AC/DC 12-30 V, 45 W. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON**

Additional Product Information

Technical data

Semiconductor Heater HG140 12-30 V AC/DC, 45 W

Model

product brand name SIVACON

product designation heater unit

design of the product Without thermostat

General technical data

operating temperature

? minimum -45 °C

? maximum 70 °C

Voltage

type of voltage / of the operating voltage AC/DC

continuous heating power / at 20 °C 45 W

inrush current / typical 3.5 A

operating voltage

? at AC / at 50 Hz / rated value / minimum 12 V

? at AC / at 50 Hz / rated value / maximum 30 V

? at AC / at 60 Hz / rated value / minimum 12 V

? at AC / at 60 Hz / rated value / maximum 30 V

? at DC / rated value / minimum 12 V

? at DC / rated value / maximum 30 V

Protection class

protection class IP IP20

Main circuit

operational current / of the slow-blow fuse link 2.5 A

Product details

product component

? blower No

? thermostat No

Connections

type of connection technology 5 x clamping terminals for stranded wire 0.5 - 1.5 mm² and solid wire 0.5 - 2.5 mm

Mechanical Design

height 105 mm

width 70 mm

depth 60 mm

fastening method Clip for 35 mm DIN rail

net weight 0.3 kg

material / of the enclosure aluminum

Environmental conditions

relative humidity / reference value 90 %

ambient temperature / during storage

? minimum -45 °C

? maximum 70 °C

Certificates

reference code / according to EN 61346-2 R

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR2130-4BA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.