

INDUSTRIAL COMPONENT DATA

8MR2150-4A SIEMENS Semiconductor heater unit CSL 028 400 W, 230 V AC clip attachment

Brand: SIEMENS | Manufacturer Part Number: 8MR2150-4A



Manufacturer	SIEMENS
MPN / Reference	8MR2150-4A
Catalog number	21504
Category	Heating (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-0F19D67629
Generated	2026-08-05

Product Overview

Semiconductor heater unit CSL 028 400 W, 230 V AC clip attachment

CALEF. CSL028, 400W,AC230V,FIJ. Paper clip. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON**

Additional Product Information

Technical data

Semiconductor heater unit CSL 028 400 W, 230 V AC clip attachment

Model

product brand name SIVACON

product designation heater unit

design of the product Semiconductor

General technical data

consumed active power / rated value 400 W

operating temperature

? minimum -45 °C

? maximum 70 °C

volume flow rate / free-blowing 45 m³/h

Voltage

type of voltage / of the operating voltage AC

continuous heating power / at 20 °C 400 W

inrush current / typical 15 A

operating voltage

? at AC / at 50 Hz / rated value / minimum 230 V

? at AC / at 50 Hz / rated value / maximum 230 V

? at AC / at 60 Hz / rated value / minimum 230 V

? at AC / at 60 Hz / rated value / maximum 230 V

Protection class

protection class IP IP20

Main circuit

operational current / of the slow-blow fuse link 10 A

Product details

product component

? blower Yes

? thermostat No

Connections

tightening torque / with screw-type terminals / maximum 0.8 N·m

type of connection technology 2-pole terminal max. 2.5 mm²

Mechanical Design

height 111 mm

width 85 mm

depth 90 mm

fastening method Clip for 35 mm DIN rail

net weight 0.5 kg

material / of the enclosure plastic

Environmental conditions

ambient temperature / during storage

? minimum -45 °C

? maximum 70 °C

Certificates

reference code / according to EN 61346-2 R

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowv...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR2150-4A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.