

INDUSTRIAL COMPONENT DATA

8MR6323-5DL40 SIEMENS Roof fan, Extract: W: 345 mm, H: 265 mm, RAL 7035, IP44, Airflow: 405 m3/h, Ue AC: 230..

Brand: SIEMENS | Manufacturer Part Number: 8MR6323-5DL40

	Manufacturer	SIEMENS
	MPN / Reference	8MR6323-5DL40
	Catalog number	63235
	Category	Ventilator (switchgear cabinet)
	Minimum order	1 Pcs
	Document ID	EO-48EB63D54F
	Generated	2026-08-06

Product Overview

Roof fan, Extract: W: 345 mm, H: 265 mm, RAL 7035, IP44, Airflow: 405 m3/h, Ue AC: 230 V
CEILING FAN CORR. OUTDOOR 405 M3 PRO H TRIMMING 345X265 MM 230 V AC RAL 7035 CONSUMPTION
POTENC. 40W GRAD. PROTECTION IP 44. Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON
--------------	---

Additional Product Information

Technical data

Roof fan, Extract: W: 345 mm, H: 265 mm, RAL 7035, IP44, Airflow: 405 m3/h, Ue AC: 230 V

Model

product brand name SIVACON

product designation Roof fans

type of ventilation ventilation

fan design / withdrawable fan No

design of the product / EMC version No

General technical data

A-rated sound power level / maximum 62 dB

consumed active power / rated value 40 W

cutout width 345 mm

cutout height 265 mm

operating period 40 000 h

rotor speed / at 50 Hz / rated value 1 430 1/min

rotor speed / at 60 Hz / rated value 1 700 1/min

type of voltage / of the operating voltage AC

operating voltage

? at AC / at 50 Hz / rated value / maximum 230 V

? at AC / at 60 Hz / rated value / maximum 230 V

Protection class

protection class IP IP44

Current

consumed current

? minimum 0.2 A

? maximum 0.21 A

Appearance

color light grey

Product details

product component / fan Yes

Number

number of ventilators 1

Mechanical Design

height 340 mm

width 420 mm

depth 108 mm

installation location Control cabinet roof

fastening method screw fixing

fastening method

? 19-inch installation No

? wall mounting No

net weight 8.1 kg

material metal

ambient temperature / during operation

? minimum -10 °C

? maximum 60 °C

Certificates

reference code / according to EN 61346-2 E

Downloads and manuals

General Product Approval other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)[ht...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR6323-5DL40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.