

INDUSTRIAL COMPONENT DATA

8MR6423-5VL60 SIEMENS Roof fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP54, Airflow: 550 m3/h, Ue AC: 230..

Brand: SIEMENS | Manufacturer Part Number: 8MR6423-5VL60



Manufacturer	SIEMENS
MPN / Reference	8MR6423-5VL60
Catalog number	64235
Category	Ventilator (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-322F4143F4
Generated	2026-08-06

Product Overview

Roof fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP54, Airflow: 550 m3/h, Ue AC: 230 V
 ROOF-FAN, AC 230V STANDARD IP54 292X292 MM RAL 7035. Manufactured to customer specifications.
 Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON

Additional Product Information

Technical data

Roof fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP54, Airflow: 550 m3/h, Ue AC: 230 V

Model

product brand name SIVACON

product designation Roof fans

type of ventilation ventilation

fan design / withdrawable fan No

design of the product / EMC version No

General technical data

A-rated sound power level / maximum 55 dB

consumed active power / rated value 64 W

cutout width 292 mm

cutout height 292 mm

operating period 40 000 h

rotor speed / at 50 Hz / rated value 0.29 1/min

rotor speed / at 60 Hz / rated value 0.35 1/min

type of voltage / of the operating voltage AC

operating voltage

? at AC / at 50 Hz / rated value / maximum 230 V

? at AC / at 60 Hz / rated value / maximum 230 V

Protection class

protection class IP IP54

Current

consumed current

? minimum 0.29 A

? maximum 0.35 A

Appearance

color light grey

Product details

product component / fan Yes

Number

number of ventilators 1

Mechanical Design

height 361 mm

width 361 mm

depth 211 mm

installation location roof

fastening method snap-on mounting

fastening method

? 19-inch installation No

? wall mounting No

net weight 4.4 kg

material plastic

ambient temperature / during operation

? minimum -10 °C

? maximum 55 °C

Certificates

reference code / according to EN 61346-2 E

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR6423-5VL60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.