

INDUSTRIAL COMPONENT DATA

8MR6523-5LV60 SIEMENS Filter fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP55, Airflow: 531 m3/h, Ue AC: 2..

Brand: SIEMENS | Manufacturer Part Number: 8MR6523-5LV60



Manufacturer	SIEMENS
MPN / Reference	8MR6523-5LV60
Catalog number	65235
Category	Ventilator (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-C46DFC327C
Generated	2026-08-06

Product Overview

Filter fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP55, Airflow: 531 m3/h, Ue AC: 230 V
 FILTER FAN CORR. OUTDOOR 531 M3 PRO H TRIMMING 292X292 MM 230 V AC RAL 7035 CONSUMPTION
 POTENC. 64W GRAD. PROTECTION IP 55. Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Power Distribution Boards SIVACON

Additional Product Information

Technical data

Filter fan, Extract: W: 292 mm, H: 292 mm, RAL 7035, IP55, Airflow: 531 m3/h, Ue AC: 230 V

Model

product brand name SIVACON

product designation filter fan

type of ventilation ventilation

fan design / withdrawable fan No

design of the product / EMC version No

General technical data

A-rated sound power level / maximum 60 dB

consumed active power / rated value 64 W

cutout width 292 mm

cutout height 292 mm

operating period 40 000 h

rotor speed / at 50 Hz / rated value 2 550 1/min

rotor speed / at 60 Hz / rated value 2 800 1/min

type of voltage / of the operating voltage AC

operating voltage

? at AC / at 50 Hz / rated value / maximum 230 V

? at AC / at 60 Hz / rated value / maximum 230 V

Protection class

protection class IP IP55

Current

consumed current

? minimum 0.29 A

? maximum 0.35 A

Appearance

color light grey

Product details

product component / fan No

Number

number of ventilators 1

Mechanical Design

height 323 mm

width 323 mm

depth 154 mm

installation location Control cabinet side panels, door, vertical

fastening method snap-on mounting

fastening method

? 19-inch installation No

? wall mounting Yes

net weight 3.4 kg

material plastic

ambient temperature / during operation

? minimum -10 °C

? maximum 55 °C

Certificates

reference code / according to EN 61346-2 E

Downloads and manuals

General Product Approval other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8MR6523-5LV60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.