

INDUSTRIAL COMPONENT DATA

8US1211-1NS10 SIEMENS Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 45 mm Bar t..

Brand: SIEMENS | Manufacturer Part Number: 8US1211-1NS10



Manufacturer	SIEMENS
MPN / Reference	8US1211-1NS10
Catalog number	12111
Category	Accessories/spare parts for busbars
Minimum order	1 Pcs
Document ID	EO-2AB23C0A48
Generated	2026-08-05

Product Overview

Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 45 mm Bar thickness: 5.10 mm+TT profile with 1 DIN rail 35 mm For 3RA6 compact load feeder Length 200 mm; Ue 690 V, IE up to 32 A, Notice: if rated current >12 A and short-circuit current > 25 kA max. conductor cross-section 6 mm² and minimum conductor length 2 m must be observed

SISTEMA DE BARRAS COLECTORAS DIST. FROM CENTER TO CENTER 60MM ADAPT. OF APPLIANCES, WIDTH: 45MM BAR THICKNESS: 5.10MM + TT PROFILE WITH 1 PROFILE SUPPORT 35MM FOR COMPACT DERIVATION 3RA6 LENGTH 200MM UE 690V, IE UP TO 32 A, ATTENTION: YES INTENSITY ASSIGNED >12A AND SHORT CIRCUIT CURRENT. > 25KA TO TAKE INTO ACCOUNT THE MAX SECTION. OF THE DRIVER 6MM² AND THE LONG. MINI. DRIVER'S 2M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SITOP Extra-fast Fuses

Additional Product Information

Additional data

Product

Article Number (Market Facing Number) 8US1211-1NS10

Product Description Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 45 mm Bar thickness: 5.10 mm+TT profile with 1 DIN rail 35 mm For 3RA6 compact load feeder Length 200 mm; Ue 690 V, IE up to 32 A, Notice:

if rated current >12 A and short-circuit current > 25 kA max. conductor cross-section 6 mm² and minimum conductor length 2 m must be observed

Product family Busbar systems

Product Lifecycle (PLM) PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group 140 / 1CU

Surcharge for Raw Materials None

Metal Factor L-P-----

Delivery information

Export Control Regulations AL : N / ECCN : N

Standard lead time ex-works 2 Day/Days

Net Weight (kg) 0,310 Kg

Packaging Dimension 81,00 x 212,00 x 71,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4011209761346

UPC 754554960432

Commodity Code 85389099

LKZ_FDB/ CatalogID LV10.1

Product Group 5888

Group Code P360

Country of origin Germany

Compliance with the substance restrictions according to RoHS directive Since: 20.02.2008

Product class A: Standard product which is a stock item could be returned within the returns guidelines/period.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Reach InformationThere is currently no information on SVHC (Substances of Very High Concern <http://ec...>)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8US1211-1NS10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.