

**INDUSTRIAL COMPONENT DATA**

# 8WA1011-1PM00 SIEMENS PEN terminal thermoplast PA6.6, Screw terminal both sides, green-yellow, 16mm Sz. 35

Brand: SIEMENS | Manufacturer Part Number: 8WA1011-1PM00



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | SIEMENS               |
| MPN / Reference | 8WA1011-1PM00         |
| Catalog number  | 10111                 |
| Category        | Ground terminal block |
| Minimum order   | 25 Pcs                |
| Document ID     | EO-894C2955C2         |
| Generated       | 2026-08-06            |

## Product Overview

PEN terminal thermoplast PA6.6, Screw terminal both sides, green-yellow, 16mm Sz. 35

PEN terminal, thermal insulating material PA6.6, screw connection on both sides, green-yellow, 16mm, size 35 ( \*\*

ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 25 Units \*\* ). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

PEN terminal thermoplast PA6.6, Screw terminal both sides, green-yellow, 16mm Sz. 35

**Model**

product brand name ALPHA

product designation PE through-type terminal

**General technical data**

insulation material thermoplastic

terminal contact spacing 16 mm

**Protection class**

combustibility class according to UL 94 V2

**Appearance**

color green-yellow

**Product details**

product feature / PEN function Yes

product component / required / end cover plate No

Number

number of terminal levels 2

number of terminal points / per terminal level 1

**Connections**

stripped length 17 mm

connectable conductor cross-section / solid

? maximum 35 mm<sup>2</sup>

connectable conductor cross-section / stranded

? maximum 35 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / maximum 35 mm<sup>2</sup>? without core end processing / maximum 35 mm<sup>2</sup>

tightening torque / with screw-type terminals

? minimum 2.5 N·m

? maximum 2.5 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

**Mechanical Design**

height / with lowest-profile installation 50 mm

length 53 mm

fastening method DIN rail 35 mm

net weight 92 g

material / of the insulating body Thermoplastic

**Environmental conditions**

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity Test Certificates

**Confirmation****Miscellaneous**

other

**Miscellaneous****Environmental Confirmations****Further information**

Information- a...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA1011-1PM00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.