


INDUSTRIAL COMPONENT DATA

8WA1011-1SF15 SIEMENS Fuse terminal Screw terminal for G fuse link 5x 20 mm and 5x 25 mm with LED 230V

Brand: SIEMENS | Manufacturer Part Number: 8WA1011-1SF15



Manufacturer	SIEMENS
MPN / Reference	8WA1011-1SF15
Catalog number	10111
Category	Fuse terminal block
Minimum order	10 Pcs
Document ID	EO-1C1BF69C66
Generated	2026-08-06

Product Overview

Fuse terminal Screw terminal for G fuse link 5x 20 mm and 5x 25 mm with LED 230V

SAFETY TERMINAL SCREW CONNECTION P. FUSE CARTRIDGE G 5X20 MM AND 5X25 MM WITH LED 230V (** ATTENTION : Price per 1 Unit and Minimum Quantity / Multipurpose Order 10 Units **). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Fuse terminal Screw terminal for G fuse link 5x 20 mm and 5x 25 mm with LED 230V

Model

product brand name ALPHA

type of light source / as defect indicator LED

design of the fuse link glass fuse 5x25 mm

design of fuse holder pluggable

General technical data

insulation material thermoplastic

terminal contact spacing 10 mm

Supply voltage

operating voltage / rated value 250 V

type of voltage / for supply of the defect indicator AC/DC

Protection class

combustibility class according to UL 94 Other

Main circuit

operational current / rated value 6.3 A

Appearance

color miscellaneous

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

Connections

connectable conductor cross-section / solid

? minimum 1 mm²

? maximum 1 mm²

connectable conductor cross-section / stranded

? maximum 1.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.75 mm²

? with core end processing / maximum 1.5 mm²

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 42 mm

length 57 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Environmental Confirmations

other

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvolt...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA1011-1SF15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.